

Product identifier:

1.1

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any

country-specific legislation (EU) 2020

316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC



316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Other means of identification: LIFT-N265-E04S-K00Q-SN97 1.2 Relevant identified uses of the substance or mixture and uses advised against: Relevant uses (Consumer use): Industrial paint Relevant uses (Professional users): Industrial paint Relevant uses (Industrial user): Industrial paint Uses advised against: All uses not specified in this section or in section 7.3 Details of the supplier of the safety data sheet: 1.3 FUPINCA C/ Londres, 13 - Pol. Ind. Cabezo Beaza 30353 Cartagena - Murcia - España Phone: +34 968089000 info@grupotkrom.com https://www.tkrom.com/ Emergency telephone number: +34 968 08 90 00 (Oficce hours) 1.4 SECTION 2: HAZARDS IDENTIFICATION ** Classification of the substance or mixture: 2.1 CLP Regulation (EC) No 1272/2008: Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008. Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400 Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410 Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 3: Flammable liquids, Category 3, H226 Skin Sens. 1: Sensitisation, skin, Category 1, H317 2.2 Label elements: CLP Regulation (EC) No 1272/2008: Warning Hazard statements: Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour. Skin Sens. 1: H317 - May cause an allergic skin reaction. **Precautionary statements:** P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P264: Wash thoroughly after handling. P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish. P501: Dispose of contents/container according to the separated collection system used in your municipality. Substances that contribute to the classification 4,4 '-Isopropylidendiphenol, Polymer Mit 2,2-Bis(p-(2,3-Epoxypropoxy)Phenyl)Propan 2.3 Other hazards: ** Changes with regards to the previous version - CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Not relevant

3.2 Mixture:

Chemical description: Mixture composed of pigments and resins

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration
CAS:	7440-66-6	Zinc powder - zinc du	st (stabilised) ⁽¹⁾ ATP CLP00	
EC: Index: REACH:	231-175-3 030-002-00-7 01-2119467174-37- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	75 - <100 %
CAS: EC:	25036-25-3 607-500-3	4,4'-Isopropylidend	iphenol, Polymer Mit 2,2-Bis(p-(2,3-Epoxypropoxy)Phenyl) Self-classified	
	Not relevant Not relevant	Regulation 1272/2008	Skin Sens. 1: H317 - Warning	5 - <10 %
CAS:	128601-23-0	Hydrocarbons, C9, arc	matics ⁽¹⁾ Self-classified	
EC: Index: REACH:	918-668-5 Not relevant 01-2119455851-35- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: 4335; STOT SE 3: H336; EUH066 - Danger	2,5 - <5 %
CAS:	Not relevant	Reaction mass of ethy	Ibenzene and m-xylene and p-xylene ⁽¹⁾ Self-classified	
	905-562-9 Not relevant 01-2119555267-33- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	1 - <2,5 %
CAS:	1330-20-7	Xylene ⁽¹⁾	Self-classified	
	215-535-7 601-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	1 - <2,5 %
CAS:	78-83-1	2-methylpropan-1-ol	ATP CLP00	
EC: Index: REACH:	201-148-0 603-108-00-1 01-2119484609-23- XXXX	Regulation 1272/2008	Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	1 - <2,5 %
CAS:	1314-13-2	zinc oxide ⁽¹⁾	ATP CLP00	
	215-222-5 030-013-00-7 01-2119463881-32- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	0,5 - <1 %
CAS:	100-41-4	Ethylbenzene ⁽²⁾	ATP ATP06	
	202-849-4 601-023-00-4 01-2119489370-35- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - 🚯 ᠢ 🔇	0,5 - <1 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 ⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
Xylene	LD50 oral	Not relevant	
	LD50 dermal	1100 mg/kg	Rat
EC: 215-535-7	LC50 inhalation vapour	17 mg/L	Rat

** Changes with regards to the previous version





316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

Identification	Acute	Acute toxicity		
Reaction mass of ethylbenzene and m-xylene and p-xylene	LD50 oral	Not relevant		
CAS: Not relevant	LD50 dermal	1100 mg/kg	Rat	
EC: 905-562-9	LC50 inhalation vapour	11 mg/L		
Ethylbenzene	LD50 oral	Not relevant		
CAS: 100-41-4	LD50 dermal	Not relevant		
EC: 202-849-4	LC50 inhalation vapour	17,2 mg/L	Rat	

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.





316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.:	5 ⁰C
Maximum Temp.:	30 °C

B.- General conditions for storage





316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 7: HANDLING AND STORAGE (continued)

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occu	Occupational exposure limits			
Reaction mass of ethylbenzene and m-xylene and p-xylene	IOELV (8h)	50 ppm	221 mg/m ³		
CAS: Not relevant EC: 905-562-9	IOELV (STEL)	100 ppm	442 mg/m ³		
Xylene (1)	IOELV (8h)	50 ppm	221 mg/m ³		
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m ³		
Ethylbenzene (1)	IOELV (8h)	100 ppm	442 mg/m ³		
CAS: 100-41-4 EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m ³		

(1) Skin

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Zinc powder - zinc dust (stabilised)	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 7440-66-6	Dermal	Not relevant	Not relevant	83 mg/kg	Not relevant
EC: 231-175-3	Inhalation	Not relevant	Not relevant	5 mg/m ³	Not relevant
Hydrocarbons, C9, aromatics	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 128601-23-0	Dermal	Not relevant	Not relevant	25 mg/kg	Not relevant
EC: 918-668-5	Inhalation	Not relevant	Not relevant	150 mg/m ³	Not relevant
Reaction mass of ethylbenzene and m-xylene and p-xylene	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: Not relevant	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
EC: 905-562-9	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
Xylene	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 1330-20-7	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
EC: 215-535-7	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
2-methylpropan-1-ol	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 78-83-1	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 201-148-0	Inhalation	Not relevant	Not relevant	Not relevant	310 mg/m ³
zinc oxide	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 1314-13-2	Dermal	Not relevant	Not relevant	83 mg/kg	Not relevant
EC: 215-222-5	Inhalation	Not relevant	Not relevant	5 mg/m ³	0,5 mg/m ³
Ethylbenzene	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 100-41-4	Dermal	Not relevant	Not relevant	180 mg/kg	Not relevant
EC: 202-849-4	Inhalation	Not relevant	293 mg/m ³	77 mg/m ³	Not relevant

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Zinc powder - zinc dust (stabilised)	Oral	Not relevant	Not relevant	0,83 mg/kg	Not relevant
CAS: 7440-66-6	Dermal	Not relevant	Not relevant	83 mg/kg	Not relevant
EC: 231-175-3	Inhalation	Not relevant	Not relevant	2,5 mg/m ³	Not relevant
Hydrocarbons, C9, aromatics	Oral	Not relevant	Not relevant	11 mg/kg	Not relevant
CAS: 128601-23-0	Dermal	Not relevant	Not relevant	11 mg/kg	Not relevant
EC: 918-668-5	Inhalation	Not relevant	Not relevant	32 mg/m ³	Not relevant





316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Lon	Long exposure	
Identification		Systemic	Local	Systemic	Local	
Reaction mass of ethylbenzene and m-xylene and p-xylene	Oral	Not relevant	Not relevant	12,5 mg/kg	Not relevant	
CAS: Not relevant	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant	
EC: 905-562-9	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³	
Xylene	Oral	Not relevant	Not relevant	12,5 mg/kg	Not relevant	
CAS: 1330-20-7	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant	
EC: 215-535-7	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³	
2-methylpropan-1-ol	Oral	Not relevant	Not relevant	Not relevant	Not relevant	
CAS: 78-83-1	Dermal	Not relevant	Not relevant	Not relevant	Not relevant	
EC: 201-148-0	Inhalation	Not relevant	Not relevant	Not relevant	55 mg/m ³	
zinc oxide	Oral	Not relevant	Not relevant	0,83 mg/kg	Not relevant	
CAS: 1314-13-2	Dermal	Not relevant	Not relevant	83 mg/kg	Not relevant	
EC: 215-222-5	Inhalation	Not relevant	Not relevant	2,5 mg/m ³	Not relevant	
Ethylbenzene	Oral	Not relevant	Not relevant	1,6 mg/kg	Not relevant	
CAS: 100-41-4	Dermal	Not relevant	Not relevant	Not relevant	Not relevant	
EC: 202-849-4	Inhalation	Not relevant	Not relevant	15 mg/m ³	Not relevant	
PNEC:						
Identification						
Zinc powder - zinc dust (stabilised)	STP	0,1 mg/L	Fresh water	(0,0206 mg/L	
CAS: 7440-66-6	Soil	106,8 mg/kg	Marine water		0,0061 mg/L	
EC: 231-175-3	Intermittent	Not relevant	Sediment (Fresh	water)	235,6 mg/kg	
	Oral	Not relevant	Sediment (Marine	e water)	121 mg/kg	
Reaction mass of ethylbenzene and m-xylene and p-xylene	STP	6,58 mg/L	Fresh water),327 mg/L	
CAS: Not relevant	Soil	2,31 mg/kg	Marine water	(),327 mg/L	
EC: 905-562-9	Intermittent	0,327 mg/L	Sediment (Fresh	water)	12,46 mg/kg	
	Oral	Not relevant	Sediment (Marine	e water)	12,46 mg/kg	
Xylene	STP	6,58 mg/L	Fresh water	(),327 mg/L	
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	(),327 mg/L	
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh	water)	12,46 mg/kg	
	Oral	Not relevant	Sediment (Marine	e water)	12,46 mg/kg	
2-methylpropan-1-ol	STP	10 mg/L	Fresh water	(),4 mg/L	
CAS: 78-83-1	Soil	0,076 mg/kg	Marine water	(),04 mg/L	
EC: 201-148-0	Intermittent	11 mg/L	Sediment (Fresh	water)	1,56 mg/kg	
	Oral	Not relevant	Sediment (Marine	e water)	0,156 mg/kg	
zinc oxide	STP	0,1 mg/L	Fresh water		0,0206 mg/L	
CAS: 1314-13-2	Soil	35,6 mg/kg	Marine water		0,0061 mg/L	
EC: 215-222-5	Intermittent	Not relevant	Sediment (Fresh	water)	117,8 mg/kg	
	Oral	Not relevant	Sediment (Marine	e water)	56,5 mg/kg	
Ethylbenzene	STP	9,6 mg/L	Fresh water),1 mg/L	
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water		0,01 mg/L	
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh	water)	13,7 mg/kg	
	Oral	0,02 g/kg	Sediment (Marine	e water)	1,37 mg/kg	

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection





316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

ION 8: EXPOSUR	E CONTRO	LS/PERSON/	AL PROTECTI	ION (conti	inued)		
Pictogram		PPE	Labelling	CEN	Standard		Remarks
Mandatory respiratory tract protection		k for gases and Filter type: A)		EN 405:20	002+A1:2010	CO CO	ace when there is a taste or smell of the ntaminant inside the face mask. If the ontaminant comes with warnings it is ommended to use isolation equipment.
C Specific protect	ion for the ha	ands					
Pictogram		PPE	Labelling	CEN	Standard		Remarks
Mandatory hand protection	mir	gloves against nor risks	CATI			prolong profession CE 21420	e gloves in case of any sign of damage. I ged periods of exposure to the product f onal users/industrials, we recommend us III gloves in line with standards EN ISO 0:2020 and EN ISO 374-1:2016+A1:2019
As the product total reliability a D Eye and face p	and has there					rial can	not be calculated in advance wit
Pictogram		PPE	Labelling	CEN	Standard		Remarks
Mandatory face protection		glasses against projections.	CAT II		66:2002 4007:2018		daily and disinfect periodically according anufacturer 's instructions. Use if there is risk of splashing.
E Body protection	1						
Pictogram		PPE	Labelling	CEN	Standard		Remarks
Mandatory complet body protection	protect	and fireproof ive clothing		EN 11 EN 114 UNE-EN I 45 EN ISO	49-1:2007 49-2:1998 49-3:2004 SO 18526-1 al :2020 14116:2015 49-5:2018		Limited protection against flames.
Mandatory foot protection	antistatic ar	ootwear with nd heat resistant operties		EN ISO EN ISO	13287:2020 20345:2022	Rep	place boots at any sign of deterioration.
F Additional eme	rgency measu	ures				1	
It is advised to situations wher						e particu	larly exposed to the product or i
Emergency r	neasure	Sta	andards	E	Emergency measu	ure	Standards
Emergency	shower		SI Z358-1 11, ISO 3864-4:20	11	Eyewash station	IS	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Environmental e	xposure cor	ntrols:					
To comply with env For more detailed i	vironmental p nformation, p	rotection regul please refer to			to prevent an	y spillag	ge of the product and its containe
Volatile organic	-		luct has the fel	lowing char	actoristics		
With regard to Dire				iowing char	acteristics:		
V.O.C. (Supply) V.O.C. density			% weight 7 kg/m³ (326,	17 a/l)			
Average carbor		7,68	, ky/11° (320,	1/ Y/L)			
Average carbor Average molect			3 g/mol				
-	-			adv to uco	has the follow	ina char	actorictics.
With regard to Dire			10 m m m m m m m m m m m m m m m m m m m		iias uie ioliow	ing char	
v.u.u. densitv	al ZU YC:	320.1	/ KU/III ³ (326.	1/ U/L)			

V.O.C. density at 20 °C: 326,17 kg/m³ (326,17 g/L)





316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

EU limit for the product (Cat. A.J): 500 g/L (2010) Components: Not relevant

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties: 9.1 For complete information see the product datasheet. **Appearance:** Physical state at 20 °C: Liquid Appearance: Viscous According to the markings on the package Colour: Odour: Not relevant * Odour threshold: Not relevant * Volatility: Boiling point at atmospheric pressure: 139 °C Vapour pressure at 20 °C: 754 Pa Vapour pressure at 50 °C: 4368,13 Pa (4,37 kPa) Evaporation rate at 20 °C: Not relevant * **Product description:** Density at 20 °C: 3155,9 kg/m³ Relative density at 20 °C: 3,156 Dynamic viscosity at 20 °C: Not relevant * Kinematic viscosity at 20 °C: Not relevant * Kinematic viscosity at 40 °C: >20,5 mm²/s Concentration: Not relevant * pH: Not relevant * Vapour density at 20 °C: Not relevant * Partition coefficient n-octanol/water 20 °C: Not relevant * Solubility in water at 20 °C: Not relevant * Solubility properties: Not relevant * Decomposition temperature: Not relevant * Melting point/freezing point: Not relevant * Flammability: 30 °C Flash Point: Flammability (solid, gas): Not relevant * Autoignition temperature: 427 °C Lower flammability limit: Not relevant * Not relevant * Upper flammability limit: **Particle characteristics:** Median equivalent diameter: Not relevant * 9.2 Other information: Information with regard to physical hazard classes: Explosive properties: Not relevant * Not relevant * Oxidising properties: Corrosive to metals: Not relevant * *Not relevant due to the nature of the product, not providing information property of its hazards.



316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)							
Heat of combustion:	Not relevant *						
Aerosols-total percentage (by mass) of flammable components: Other safety characteristics:	Not relevant *						
Surface tension at 20 °C:	Not relevant *						
Refraction index:	Not relevant *						
*Not relevant due to the nature of the product, not providing inf	*Not relevant due to the nature of the product, not providing information property of its hazards.						

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.

- Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- IARC: Xylene (3); Ethylbenzene (2B); Hydrocarbons, C9, aromatics (3); Reaction mass of ethylbenzene and m-xylene and p -xylene (3); Zeolites (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.

- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute	toxicity	Genus
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg	Rat
EC: 215-535-7	LC50 inhalation vapour	17 mg/L	Rat
Hydrocarbons, C9, aromatics	LD50 oral	>3492 mg/kg	Rat
CAS: 128601-23-0	LD50 dermal		
EC: 918-668-5	LC50 inhalation		
	LC50 inhalation vapour		
Reaction mass of ethylbenzene and m-xylene and p-xylene	LD50 oral	2100 mg/kg	Rat
CAS: Not relevant	LD50 dermal	1100 mg/kg	Rat
EC: 905-562-9	LC50 inhalation vapour	11 mg/L	
-methylpropan-1-ol	LD50 oral	3350 mg/kg	Rat
CAS: 78-83-1	LD50 dermal	2460 mg/kg	Rabbit
EC: 201-148-0	LC50 inhalation vapour	24,6 mg/L (4 h)	Rat
zinc oxide	LD50 oral	7950 mg/kg	Mouse
CAS: 1314-13-2	LD50 dermal		
EC: 215-222-5	LC50 inhalation		
	LC50 inhalation dust		
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation vapour	17,2 mg/L	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information



Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any

country-specific legislation



316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Very toxic to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Zinc powder - zinc dust (stabilised)	LC50	0,31 mg/L (96 h)	N/A	Fish
CAS: 7440-66-6	EC50	1,22 mg/L (48 h)	Daphnia magna	Crustacean
EC: 231-175-3	EC50	Not relevant		
Hydrocarbons, C9, aromatics	LC50	>1 - 10 mg/L (96 h)		Fish
CAS: 128601-23-0	EC50	>1 - 10 mg/L (48 h)		Crustacean
EC: 918-668-5	EC50	>1 - 10 mg/L (72 h)		Algae
Reaction mass of ethylbenzene and m-xylene and p-xylene	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: Not relevant	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: 905-562-9	EC50	>10 - 100 mg/L (72 h)		Algae
Xylene	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 1330-20-7	EC50	>10 - 100 mg/L (48 h)		Crustacean
EC: 215-535-7	EC50	>10 - 100 mg/L (72 h)		Algae
2-methylpropan-1-ol	LC50	2030 mg/L (96 h)	Carassius auratus	Fish
CAS: 78-83-1	EC50	1439 mg/L (48 h)	Daphnia magna	Crustacear
EC: 201-148-0	EC50	1250 mg/L (48 h)	Scenedesmus subspicatus	Algae
zinc oxide	LC50	0,82 mg/L (96 h)	Oncorhynchus kisutch	Fish
CAS: 1314-13-2	EC50	3,4 mg/L (48 h)	Daphnia magna	Crustacean
EC: 215-222-5	EC50	Not relevant		
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacear
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae

Chronic toxicity:

Identification		Concentration	Species	Genus
Zinc powder - zinc dust (stabilised)	NOEC	0,44 mg/L	Oncorhynchus mykiss	Fish
CAS: 7440-66-6 EC: 231-175-3	NOEC	0,031 mg/L	Daphnia magna	Crustacean
Reaction mass of ethylbenzene and m-xylene and p-xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: Not relevant EC: 905-562-9	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
2-methylpropan-1-ol	NOEC	Not relevant		
CAS: 78-83-1 EC: 201-148-0	NOEC	20 mg/L	Daphnia magna	Crustacean
zinc oxide	NOEC	0,44 mg/L	Oncorhynchus mykiss	Fish
CAS: 1314-13-2 EC: 215-222-5	NOEC	0,031 mg/L	Daphnia magna	Crustacean
Ethylbenzene	NOEC	Not relevant		
CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradab	ility
Reaction mass of ethylbenzene and m-xylene and p-xylene	BOD5	Not relevant	Concentration	Not relevant
CAS: Not relevant	COD	Not relevant	Period	28 days
EC: 905-562-9	BOD5/COD	Not relevant	% Biodegradable	88 %





316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	De	egradability	Biod	Biodegradability	
Xylene	BOD5	Not relevant	Concentration	Not relevant	
CAS: 1330-20-7	COD	Not relevant	Period	28 days	
EC: 215-535-7	BOD5/COD	Not relevant	% Biodegradable	88 %	
2-methylpropan-1-ol	BOD5	0,4 g O2/g	Concentration	100 mg/L	
CAS: 78-83-1	COD	2,41 g O2/g	Period	14 days	
EC: 201-148-0	BOD5/COD	0,17	% Biodegradable	90 %	
Ethylbenzene	BOD5	Not relevant	Concentration	100 mg/L	
CAS: 100-41-4	COD	Not relevant	Period	14 days	
EC: 202-849-4	BOD5/COD	Not relevant	% Biodegradable	90 %	

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccu	Bioaccumulation potential		
Reaction mass of ethylbenzene and m-xylene and p-xylene	BCF	9		
CAS: Not relevant	Pow Log	2.77		
EC: 905-562-9	Potential	Low		
Xylene	BCF	9		
CAS: 1330-20-7	Pow Log	2.77		
EC: 215-535-7	Potential	Low		
2-methylpropan-1-ol	BCF	3		
CAS: 78-83-1	Pow Log	0.76		
EC: 201-148-0	Potential	Low		
Ethylbenzene	BCF	1		
CAS: 100-41-4	Pow Log	3.15		
EC: 202-849-4	Potential	Low		

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Reaction mass of ethylbenzene and m-xylene and p-xylene	Кос	202	Henry	524,86 Pa·m ³ /mol
CAS: Not relevant	Conclusion	Moderate	Dry soil	Yes
EC: 905-562-9	Surface tension	Not relevant	Moist soil	Yes
Xylene	Кос	202	Henry	524,86 Pa·m ³ /mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Not relevant	Moist soil	Yes
2-methylpropan-1-ol	Кос	Not relevant	Henry	Not relevant
CAS: 78-83-1	Conclusion	Not relevant	Dry soil	Not relevant
EC: 201-148-0	Surface tension	2,378E-2 N/m (25 °C)	Moist soil	Not relevant
Ethylbenzene	Кос	520	Henry	798,44 Pa·m ³ /mol
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous



316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2025 and RID 2025:

With regard to A	DR 202	25 and RID 2025:	
	14.1	UN number or ID number:	UN1263
× ×	14.2	UN proper shipping name:	PAINT
	14.3	Transport hazard class(es):	3
		Labels:	3
		Packing group:	III
		Environmental hazards:	Yes
	14.6	Special precautions for user	
		Special regulations:	163, 367, 650
		Tunnel restriction code:	D/E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
	14.7	Maritime transport in bulk according to IMO instruments:	Not relevant
Transport of da	ngero	us goods by sea:	
With regard to IM	1DG 41	-22:	
	14.1	UN number or ID number:	UN1263
	14.2	UN proper shipping name:	PAINT
<u> </u>	14.3	Transport hazard class(es):	3
		Labels:	3
▼ ∨	14.4	Packing group:	III
	14.5	Marine pollutant:	Yes
	14.6	Special precautions for user	
		Special regulations:	223, 955, 163, 367
		EmS Codes:	F-E, S-E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
		Segregation group:	Not relevant
	14.7	Maritime transport in bulk according to IMO	Not relevant
Transport of da	naero	instruments: us goods by air:	

With regard to IATA/ICAO 2025:



316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC



SECTION 14: TRANSPORT INFORMATION (continued) UN1263 14.1 UN number or ID number: 14.2 UN proper shipping name: PAINT 14.3 Transport hazard class(es): 3 Labels: 3 14.4 Packing group: III 14.5 Environmental hazards: Yes 14.6 Special precautions for user Physico-Chemical properties: see section 9 14.7 Maritime transport in bulk Not relevant according to IMO instruments:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
E1	ENVIRONMENTAL HAZARDS	100	200

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Laboral exposure to respirable crystalline silica must be controlled in accordance with Directive (EU) 2022/431, of the European Parliament and of the Council, of March 9, 2022, amending Directive 2004/37/EC, relating to the protection of workers against risks related to exposure to carcinogens or mutagens during work.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

Removed substances

Quartz (RCS < 1 %) (14808-60-7)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

Precautionary statements



316110001 - PROTEK EPOXI PRIMER 1711 RICA EN ZINC

SECTION 16: OTHER INFORMATION (continued)

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction.

H410: Very toxic to aquatic life with long lasting effects.

H400: Very toxic to aquatic life.

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled. Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Skin Sens. 1: Calculation method Aquatic Chronic 1: Calculation method Aquatic Acute 1: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

- ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation
- COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.