

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

216030099 - REVESTIMIENTO PETREO BLANCO R53

Other means of identification:

UFI:

T8O9-X091-R00V-Y3VK

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses (Consumer use): Waterproofing agents for terraces and facades Relevant uses (Professional users): Waterproofing agents for terraces and facades Relevant uses (Industrial user): Waterproofing agents for terraces and facades Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

EUPINCA C/ Londres, 13 - Pol. Ind. Cabezo Beaza 30353 Cartagena - Murcia - España Phone: +34 968089000 info@grupotkrom.com https://www.tkrom.com/

1.4 Emergency telephone number: +34 968 08 90 00 (Oficce hours)

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

- P102: Keep out of reach of children.
- P273: Avoid release to the environment.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

Supplementary information:

EUH208: Contains Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

2.3 Other hazards:

Product does not meet PBT/vPvB criteria Endocrine-disrupting properties: The product does not meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Not relevant

3.2 Mixture:

Chemical description: Aqueous mixture composed of additives, aggregates, coalescents, pigments and resins

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

** Changes with regards to the previous version



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

	Identification		Chemical name/Classification	Concentration
CAS:	Not relevant	Hydrocarbons, C9-C11	,n-alkanes, iso-alkanes, cyclics, <2% aromatics ⁽¹⁾ Self-classified	
EC: 919-857-5 Index: Not relevant REACH: 01-2119463258-33- XXXX		Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger 🔅 🕐 🔇	1 - <2,5 %
CAS:	330-54-1	diuron (ISO) ⁽¹⁾	ATP ATP21	
Index: (REACH: (206-354-4 006-015-00-9 01-2119517622-45- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Carc. 1B: H350; STOT RE 2: H373 - Danger	<1 %
CAS:	13463-41-7	Pyrithione zinc ⁽¹⁾	ATP ATP15	
EC: Index: REACH:	236-671-3 613-333-00-7 01-2119511196-46- XXXX	Regulation 1272/2008	Acute Tox. 2: H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Repr. 1B: H360D; STOT RE 1: H372 - Danger	<1 %
CAS: EC: Index: REACH:	55965-84-9 Not relevant	Reaction mass of 5-c -3-one (3:1) ⁽¹⁾	hloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol ATP ATP13	
	613-167-00-5 Not relevant	Regulation 1272/2008	Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger	<1 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

	Identification			M-factor	
diuron (ISO)			Acute	100	
CAS: 330-54-1	EC: 206-354-4		Chronic	100	
Pyrithione zinc			Acute	1000	
CAS: 13463-41-7	AS: 13463-41-7 EC: 236-671-3			10	
Reaction mass of 5-c	Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothia		Acute	100	
AS: 55965-84-9 EC: Not relevant			Chronic	100	
	Identification Specific concentration limit				
Reaction mass of E	bloro_2_methyl_2H_icothiazol_3_one and 2_methyl_2H_	0/((w/w)) > -0.6 Claim Comm	10 11214		

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-	% (w/w) >=0,6: Skin Corr. 1C - H314
isothiazol-3-one (3:1)	0,06<= % (w/w) <0,6: Skin Irrit. 2 - H315
CAS: 55965-84-9	% (w/w) >=0,6: Eye Dam. 1 - H318
EC: Not relevant	0,06<= % (w/w) <0,6: Eye Irrit. 2 - H319
	% (w/w) >=0.0015: Skin Sens. 1A - H317

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute	Acute toxicity		
diuron (ISO)	LD50 oral	1017 mg/kg	Rat	
CAS: 330-54-1 EC: 206-354-4	LD50 dermal	Not relevant		
	LC50 inhalation vapour	Not relevant		
Pyrithione zinc	LD50 oral	300 mg/kg	Rat	
CAS: 13463-41-7	LD50 dermal	Not relevant		
EC: 236-671-3	LC50 inhalation vapour	0,8 mg/L *		
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H- isothiazol-3-one (3:1)	LD50 oral	64 mg/kg	Rat	
CAS: 55965-84-9	LD50 dermal	87,12 mg/kg	Rabbit	
EC: Not relevant	LC50 inhalation vapour	0,5 mg/L		

* Equivalent ATE value of the substance applicable to the exposure route of the product. For the ATE value associated with the exposure route of the substance, see section 11.

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:**



SECTION 4: FIRST AID MEASURES (continued)

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

- A.- Specific storage requirements
 - Minimum Temp.: 5 °C
 - Maximum Temp.: 30 °C
- B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long e	exposure
Identification		Systemic	Local	Systemic	Local
diuron (ISO)	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 330-54-1	Dermal	Not relevant	Not relevant	5,79 mg/kg	Not relevant
EC: 206-354-4	Inhalation	Not relevant	Not relevant	0,17 mg/m ³	Not relevant
Pyrithione zinc	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 13463-41-7	Dermal	Not relevant	Not relevant	0,01 mg/kg	Not relevant
EC: 236-671-3	Inhalation	Not relevant	Not relevant	Not relevant	Not relevant

DNEL (General population):

Not relevant

PNEC:

Identification				
diuron (ISO)	STP	58 mg/L	Fresh water	0,00032 mg/L
CAS: 330-54-1	Soil	0,012 mg/kg	Marine water	0,000032 mg/L
EC: 206-354-4	Intermittent	0,00022 mg/L	Sediment (Fresh water)	0,052 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,005 mg/kg
Pyrithione zinc	STP	0,01 mg/L	Fresh water	0,00009 mg/L
CAS: 13463-41-7	Soil	1,02 mg/kg	Marine water	0,00009 mg/L
EC: 236-671-3	Intermittent	Not relevant	Sediment (Fresh water)	0,009 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,009 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

If the working conditions and/or safety measures adopted do not allow keeping the airborne concentration of the product below the exposure limits (if any) or at acceptable levels (if no exposure limits exist), suitable respiratory protection equipment chosen by a qualified professional should be used.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E	Body protection				

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.





This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

216030099 - REVESTIMIENTO PETREO BLANCO R53

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued) Pictogram PPE Labelling **CEN Standard** Remarks Replace before any evidence of deterioration. For periods of prolonged exposure to the product for Anti-slip work shoes EN ISO 20347:2022 professional/industrial users CE III is recommended, in accordance with the regulations **CAT II** in EN ISO 20345:2022 y EN 13832-1:2019 F.- Additional emergency measures It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments. Emergency measure Standards Emergency measure Standards **0**+ ANSI Z358-1 DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 ISO 3864-1:2011, ISO 3864-4:2011 Eyewash stations Emergency shower **Environmental exposure controls:** To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D. Volatile organic compounds: With regard to Directive 2010/75/EU, this product has the following characteristics: 1,51 % weight V.O.C. (Supply): 24,59 kg/m3 (24,59 g/L) V.O.C. density at 20 °C: Average carbon number: 9,94 Average molecular weight: 145,77 g/mol With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics: V.O.C. density at 20 °C: 24,59 kg/m3 (24,59 g/L) EU limit for the product (Cat. A.C): 40 g/L (2010) Components: Not relevant

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1	Information on basic physical and chemical properties:						
	For complete information see the product datasheet.						
	Appearance:						
	Physical state at 20 °C:	Liquid					
	Appearance:	Viscous					
	Colour:	According to the markings on the package					
	Odour:	Characteristic					
	Odour threshold:	Not relevant *					
	Volatility:						
	Boiling point at atmospheric pressure:	104 °C					
	Vapour pressure at 20 °C:	2331 Pa					
	Vapour pressure at 50 °C:	12285,37 Pa (12,29 kPa)					
	Evaporation rate at 20 °C:	Not relevant *					
	Product description:						
	Density at 20 °C:	1623,3 kg/m³					
	Relative density at 20 °C:	1,623					
	Dynamic viscosity at 20 °C:	Not relevant *					
	Kinematic viscosity at 20 °C:	Not relevant *					
	*Not relevant due to the nature of the product, not providing	ng information property of its hazards.					



SEC	TION 9: PHYSICAL AND CHEMICAL PROPERTIES	S (continued)
	Kinematic viscosity at 40 °C:	>20,5 mm²/s
	Concentration:	Not relevant *
	pH:	8
	Vapour density at 20 °C:	Not relevant *
	Partition coefficient n-octanol/water 20 °C:	Not relevant *
	Solubility in water at 20 °C:	Not relevant *
	Solubility properties:	Not relevant *
	Decomposition temperature:	Not relevant *
	Melting point/freezing point:	Not relevant *
	Flammability:	
	Flash Point:	Non Flammable (>60 °C)
	Flammability (solid, gas):	Not relevant *
	Autoignition temperature:	260 °C
	Lower flammability limit:	Not relevant *
	Upper flammability limit:	Not relevant *
	Particle characteristics:	
	Median equivalent diameter:	Not relevant *
9.2	Other information:	
	Information with regard to physical hazard clas	ses:
	Explosive properties:	Not relevant *
	Oxidising properties:	Not relevant *
	Corrosive to metals:	Not relevant *
	Heat of combustion:	Not relevant *
	Aerosols-total percentage (by mass) of flammable components:	Not relevant *
	Other safety characteristics:	
	Surface tension at 20 °C:	Not relevant *
	Refraction index:	Not relevant *
	*Not relevant due to the nature of the product, not providing infor	mation property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:



SECTION 10: STABILITY AND REACTIVITY (continued)

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO_2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.

- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.

IARC: Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 (3); Talc (3); Hydrocarbons, C9-C11,n-alkanes, iso -alkanes, cyclics, <2% aromatics (3); 2,2[']-iminodiethanol (2B)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

** Changes with regards to the previous version



SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Not relevant

Specific toxicology information on the substances:

Identification	Acute	toxicity	Genus
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics	LD50 oral	>5000 mg/kg	Rat
CAS: Not relevant EC: 919-857-5	LD50 dermal		
	LC50 inhalation		
diuron (ISO)	LD50 oral	1017 mg/kg	Rat
CAS: 330-54-1 EC: 206-354-4	LD50 dermal		
	LC50 inhalation		
Pyrithione zinc CAS: 13463-41-7 EC: 236-671-3	LD50 oral	300 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation mist	0,14 mg/L	Rat
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H- isothiazol-3-one (3:1)	LD50 oral	64 mg/kg	Rat
CAS: 55965-84-9 EC: Not relevant	LD50 dermal	87,12 mg/kg	Rabbit
	LC50 inhalation	100,01 mg/L	
	LC50 inhalation vapour	0,5 mg/L	
	LC50 inhalation dust	0,05 mg/L	
	LC50 inhalation mist	0,05 mg/L	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
diuron (ISO)	LC50	6,6 mg/L (96 h)	Leuciscus idus	Fish
CAS: 330-54-1	EC50	1,4 mg/L (48 h)	Daphnia magna	Crustacean
EC: 206-354-4	EC50	0,022 mg/L (96 h)	Scenedesmus subspicatus	Algae
Pyrithione zinc	LC50	0,003 mg/L (96 h)	Pimephales promelas	Fish
CAS: 13463-41-7	EC50	0,008 mg/L (48 h)	Daphnia magna	Crustacean
EC: 236-671-3	EC50	Not relevant		
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2- methyl-2H-isothiazol-3-one (3:1)	LC50	>0.001 - 0.01 mg/L (96 h)		Fish
CAS: 55965-84-9	EC50	>0.001 - 0.01 mg/L (48 h)		Crustacean
EC: Not relevant	EC50	>0.001 - 0.01 mg/L (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
diuron (ISO)	NOEC	>0.001 - 0.01 mg/L		Fish
CAS: 330-54-1 EC: 206-354-4	NOEC	>0.001 - 0.01 mg/L		Crustacean
Pyrithione zinc	NOEC	Not relevant		
CAS: 13463-41-7 EC: 236-671-3	NOEC	0,022 mg/L	Daphnia magna	Crustacean

** Changes with regards to the previous version



Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

216030099 - REVESTIMIENTO PETREO BLANCO R53

SECTION 12: ECOLOGICAL INFORMATION ** (continued) Identification Concentration Species Genus Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-NOFC >0.001 - 0.01 mg/L Fish methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Not relevant NOEC >0.001 - 0.01 mg/L Crustacean 12.2 Persistence and degradability: Substance-specific information: Identification Degradability Biodegradability Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% BOD5 Not relevant Not relevant Concentration aromatics CAS: Not relevant COD Not relevant Period 28 days EC: 919-857-5 BOD5/COD Not relevant % Biodegradable 80 % BOD5 100 mg/L diuron (ISO) Not relevant Concentration COD 28 days CAS: 330-54-1 Not relevant Period EC: 206-354-4 BOD5/COD % Biodegradable 0 % Not relevant 12.3 Bioaccumulative potential: Substance-specific information: Identification Bioaccumulation potential diuron (ISO) BCF 64 CAS: 330-54-1 Pow Log 2.68 EC: 206-354-4 Potential Moderate 12.4 Mobility in soil: Not relevant 12.5 Results of PBT and vPvB assessment: Product does not meet PBT/vPvB criteria 12.6 Endocrine disrupting properties: Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous	

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)



SECTION 15: REGULATORY INFORMATION **

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione, (ethylenedioxy)dimethanol, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3one, octhilinone (ISO), diuron (ISO), Pyrithione zinc.

- Article 95, REGULATION (EU) No 528/2012: diuron (ISO) (330-54-1) - PT: (7,10); Pyrithione zinc (13463-41-7) - PT: (2,6,7,9,10,21); Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9) - PT: (2,4,6,11,12,13); Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione (5395-50-6) - PT: (6,11,12,13); (ethylenedioxy)dimethanol (3586-55-8) - PT: (6,11,12,13); 1,2-benzisothiazol-3(2H)-one (2634-33-5) - PT: (2,6,9,11,12,13); 2-methyl-2H-isothiazol-3-one (2682-20-4) - PT: (6,11,12,13); octhilinone (ISO) (26530-20-1) - PT: (6,7,8,9,10,11,13)

- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: diuron (ISO) (330-54-1)
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Not relevant

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

** Changes with regards to the previous version

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

· New declared substances

diuron (ISO) (330-54-1)

Pyrithione zinc (13463-41-7)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

Hazard statements

Precautionary statements

REGULATORY INFORMATION (SECTION 15):

· Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc)

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

** Changes with regards to the previous version



SECTION 16: OTHER INFORMATION ** (continued)	
 Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled. Acute Tox. 2: H330 - Fatal if inhaled. Acute Tox. 3: H301 - Toxic if swallowed. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Carc. 1B: H350 - May cause cancer. Eye Dam. 1: H318 - Causes serious eye damage. Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 1B: H360D - May damage the unborn child. Skin Corr. 1C: H314 - Causes severe skin burns and eye damage. Skin Sens. 1A: H317 - May cause an allergic skin reaction. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure. STOT SE 3: H336 - May cause drowsiness or dizziness. 	
Classification procedure: Aquatic Chronic 3: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehensic interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu	on and
http://eur-lex.europa.eu Abbreviations and acronyms: ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LC50: Lethal Concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon	
UFI: unique formula identifier IARC: International Agency for Research on Cancer	

** Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.