

**406200001 - CATALIZADOR ESMALTE TKROM GLASS COMPONENTE B**



**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1 Product identifier:** 406200001 - CATALIZADOR ESMALTE TKROM GLASS COMPONENTE B

**Other means of identification:**

**UFI:** X0X4-U08F-T006-KJH5

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: Industrial paint. For professional users/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

EUPINCA

C/ Londres, 13 - Pol. Ind. Cabezo Beaza

30353 Cartagena - Murcia - España

Phone: +34 968089000

info@grupotkrom.com

https://www.tkrom.com/

**1.4 Emergency telephone number:** +34 968 08 90 00 (Oficce hours)

**SECTION 2: HAZARDS IDENTIFICATION \*\***

**2.1 Classification of the substance or mixture:**

**CLP Regulation (EC) No 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute toxicity, Category 4, H312+H332

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Irrit. 2: Eye irritation, Category 2, H319

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

**2.2 Label elements:**

**CLP Regulation (EC) No 1272/2008:**

**Warning**



**Hazard statements:**

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). Organs affected: All gross lesions and masses.

STOT SE 3: H335 - May cause respiratory irritation.

**Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)**

**Supplementary information:**

EUH204: Contains isocyanates. May produce an allergic reaction.

**Substances that contribute to the classification**

Hexamethylene diisocyanate, oligomers; Reaction mass of ethylbenzene and m-xylene and p-xylene ; Hydrocarbons, C9, aromatics; Hexamethylene-di-isocyanate

**Additional Labelling:**

As from 24 August 2023 adequate training is required before industrial or professional use.

**2.3 Other hazards:**

Product does not meet PBT/vPvB criteria  
Endocrine-disrupting properties: The product does not meet the criteria.

\*\* Changes with regards to the previous version

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**

Non-applicable

**3.2 Mixture:**

**Chemical description:** Mixture composed of additives, pigments and resins

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 28182-81-2 EC: 931-274-8 Index: Non-applicable REACH: 01-2119485796-17-XXXX	<b>Hexamethylene diisocyanate, oligomers</b> <sup>1</sup>	Self-classified	50 - <75 %
	Regulation 1272/2008	Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning	
CAS: Non-applicable EC: 905-562-9 Index: Non-applicable REACH: 01-2119555267-33-XXXX	<b>Reaction mass of ethylbenzene and m-xylene and p-xylene</b> <sup>1</sup>	Self-classified	10 - <25 %
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	<b>2-methoxy-1-methylethyl acetate</b> <sup>2</sup>	ATP ATP01	2,5 - <10 %
	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning	
CAS: 128601-23-0 EC: 918-668-5 Index: Non-applicable REACH: 01-2119455851-35-XXXX	<b>Hydrocarbons, C9, aromatics</b> <sup>1</sup>	Self-classified	2,5 - <10 %
	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	
CAS: 822-06-0 EC: 212-485-8 Index: 615-011-00-1 REACH: 01-2119457571-37-XXXX	<b>Hexamethylene-di-isocyanate</b> <sup>1</sup>	Self-classified	<1 %
	Regulation 1272/2008	Acute Tox. 1: H330; Acute Tox. 4: H302; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	

<sup>1</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

<sup>2</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**Other information:**

Identification	Specific concentration limit
Hexamethylene-di-isocyanate CAS: 822-06-0 EC: 212-485-8	% (w/w) >=0,5: Resp. Sens. 1 - H334 % (w/w) >=0,5: Skin Sens. 1 - H317

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:



**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Non-applicable	1100 mg/kg (ATEi)	Rat
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	11 mg/L (ATEi)	Non-applicable	
	Non-applicable	11 mg/L (ATEi)	

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media:**

**Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

**Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

- CONTINUED ON NEXT PAGE -



## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

#### A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

#### B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

#### C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

#### D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

### 7.2 Conditions for safe storage, including any incompatibilities:

#### A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

#### B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	IOELV (8h)	50 ppm
	IOELV (STEL)	100 ppm	550 mg/m <sup>3</sup>

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	1 mg/m <sup>3</sup>	Non-applicable	0,5 mg/m <sup>3</sup>
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
	Inhalation	Non-applicable	550 mg/m <sup>3</sup>	275 mg/m <sup>3</sup>	Non-applicable
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	150 mg/m <sup>3</sup>	Non-applicable
Hexamethylene-di-isocyanate CAS: 822-06-0 EC: 212-485-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	0,07 mg/m <sup>3</sup>	Non-applicable	0,035 mg/m <sup>3</sup>

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	33 mg/m <sup>3</sup>	33 mg/m <sup>3</sup>
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	Oral	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	32 mg/m <sup>3</sup>	Non-applicable

**PNEC:**

Identification		Fresh water		Marine water	
		STP	Intermittent	STP	Intermittent
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	Soil	88 mg/L	53183 mg/kg	0,127 mg/L	0,013 mg/L
	Soil	1,27 mg/L	266701 mg/kg	266701 mg/kg	266701 mg/kg
	Soil	Non-applicable	26670 mg/kg	26670 mg/kg	26670 mg/kg
	Soil	Non-applicable	26670 mg/kg	26670 mg/kg	26670 mg/kg
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Soil	6,58 mg/L	2,31 mg/kg	0,327 mg/L	0,327 mg/L
	Soil	0,327 mg/L	0,327 mg/L	12,46 mg/kg	12,46 mg/kg
	Soil	Non-applicable	12,46 mg/kg	12,46 mg/kg	12,46 mg/kg
	Soil	Non-applicable	12,46 mg/kg	12,46 mg/kg	12,46 mg/kg
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Soil	100 mg/L	0,29 mg/kg	0,635 mg/L	0,064 mg/L
	Soil	0,29 mg/kg	6,35 mg/L	3,29 mg/kg	3,29 mg/kg
	Soil	Non-applicable	3,29 mg/kg	3,29 mg/kg	3,29 mg/kg
	Soil	Non-applicable	3,29 mg/kg	3,29 mg/kg	3,29 mg/kg

- CONTINUED ON NEXT PAGE -

**406200001 - CATALIZADOR ESMALTE TKROM GLASS COMPONENTE B**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification				
Hexamethylene-di-isocyanate	STP	8,42 mg/L	Fresh water	Non-applicable
CAS: 822-06-0	Soil	Non-applicable	Marine water	Non-applicable
EC: 212-485-8	Intermittent	Non-applicable	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

**8.2 Exposure controls:**

**A.- Individual protection measures, such as personal protective equipment**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	<b>CE</b> CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	<b>CE</b> CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	<b>CE</b> CAT II	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	<b>CE</b> CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	<b>CE</b> CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

- CONTINUED ON NEXT PAGE -



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	39,84 % weight
V.O.C. density at 20 °C:	406,8 kg/m <sup>3</sup> (406,8 g/L)
Average carbon number:	7,63
Average molecular weight:	114,39 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	406,8 kg/m <sup>3</sup> (406,8 g/L)
EU limit for the product (Cat. A.J):	500 g/L (2010)
Components:	Non-applicable

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Characteristic
Colour:	Colourless
Odour:	Not available
Odour threshold:	Non-applicable *

#### Volatility:

Boiling point at atmospheric pressure:	142 °C
Vapour pressure at 20 °C:	604 Pa
Vapour pressure at 50 °C:	3411,45 Pa (3,41 kPa)
Evaporation rate at 20 °C:	Non-applicable *

#### Product description:

Density at 20 °C:	1021,1 kg/m <sup>3</sup>
Relative density at 20 °C:	1,021
Dynamic viscosity at 20 °C:	3000 cP
Kinematic viscosity at 20 °C:	2938,08 mm <sup>2</sup> /s
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

#### Flammability:

Flash Point:	31 °C
--------------	-------

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Flammability (solid, gas): Non-applicable \*  
 Autoignition temperature: 315 °C  
 Lower flammability limit: Not available  
 Upper flammability limit: Not available

**Particle characteristics:**

Median equivalent diameter: Non-applicable

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties: Non-applicable \*  
 Oxidising properties: Non-applicable \*  
 Corrosive to metals: Non-applicable \*  
 Heat of combustion: Non-applicable \*  
 Aerosols-total percentage (by mass) of flammable components: Non-applicable \*

**Other safety characteristics:**

Surface tension at 20 °C: Non-applicable \*  
 Refraction index: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- CONTINUED ON NEXT PAGE -





**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
  - Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Reaction mass of ethylbenzene and m-xylene and p-xylene (3); Hydrocarbons, C9, aromatics (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
  - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) - single exposure:
 

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness. Organs affected: All gross lesions and masses.
  - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:
 

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEI)	Rat
	LC50 inhalation	11 mg/L (ATEI)	
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	LD50 oral	5100 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	11 mg/L (ATEI)	
Hexamethylene-di-isocyanate CAS: 822-06-0 EC: 212-485-8	LD50 oral	959 mg/kg	Rat
	LD50 dermal	7000 mg/kg	Rat
	LC50 inhalation	0,12 mg/L (4 h)	Rat

**11.2 Information on other hazards:**

- CONTINUED ON NEXT PAGE -



**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

**Endocrine disrupting properties**

Endocrine-disrupting properties: The product does not meet the criteria.

**Other information**

Non-applicable

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

**12.1 Toxicity:**

**Acute toxicity:**

Identification	Concentration		Species	Genus
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	LC50	Non-applicable		
	EC50	Non-applicable		
	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	LC50	>10 - 100 mg/L (96 h)		Fish
	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50	Non-applicable		
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae

**Chronic toxicity:**

Identification	Concentration		Species	Genus
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	NOEC	47,5 mg/L	Oryzias latipes	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:**

**Substance-specific information:**

Identification	Degradability		Biodegradability	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Non-applicable	Concentration	785 mg/L
	COD	Non-applicable	Period	8 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

Identification	Bioaccumulation potential	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	BCF	9
	Pow Log	2.77
	Potential	Low
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Pow Log	0.43
	Potential	Low

**12.4 Mobility in soil:**

- CONTINUED ON NEXT PAGE -



**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Absorption/desorption		Volatility	
Reaction mass of ethylbenzene and m-xylene and p-xylene	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol
CAS: Non-applicable	Conclusion	Moderate	Dry soil	Yes
EC: 905-562-9	Surface tension	Non-applicable	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

Product does not meet PBT/vPvB criteria

**12.6 Endocrine disrupting properties:**

Endocrine-disrupting properties: The product does not meet the criteria.

**12.7 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2023 and RID 2023:



- 14.1 UN number or ID number:** UN1866
- 14.2 UN proper shipping name:** RESIN SOLUTION
- 14.3 Transport hazard class(es):** 3
- Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Special regulations: Non-applicable
- Tunnel restriction code: D/E
- Physico-Chemical properties: see section 9
- Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 40-20:



**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number or ID number:** UN1866
- 14.2 UN proper shipping name:** RESIN SOLUTION
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**  
Special regulations: 955, 223  
EmS Codes: F-E, S-E  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2023:



- 14.1 UN number or ID number:** UN1866
- 14.2 UN proper shipping name:** RESIN SOLUTION
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable  
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable  
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable  
Article 95, REGULATION (EU) No 528/2012: Non-applicable  
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**



## 406200001 - CATALIZADOR ESMALTE TKROM GLASS COMPONENTE B

### SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains more than 0.1 % of Hexamethylene-di-isocyanate, Hexamethylene diisocyanate, oligomers by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s).

2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".

3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks.

4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:

(a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).

(b) the training elements in points (a) and (b) of paragraph 5 for the following uses:

- handling open mixtures at ambient temperature (including foam tunnels)
- spraying in a ventilated booth
- application by roller
- application by brush
- application by dipping and pouring
- mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore
- cleaning and waste
- any other uses with similar exposure through the dermal and/or inhalation route

(c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:

- handling incompletely cured articles (e.g. freshly cured, still warm)
- foundry applications
- maintenance and repair that needs access to equipment
- open handling of warm or hot formulations (> 45 °C)
- spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers)
- and any other uses with similar exposure through the dermal and/or inhalation route.

5. Training elements:

(a) general training, including on-line training, on:

- chemistry of diisocyanates
- toxicity hazards (including acute toxicity)
- exposure to diisocyanates
- occupational exposure limit values
- how sensitisation can develop
- odour as indication of hazard
- importance of volatility for risk
- viscosity, temperature, and molecular weight of diisocyanates
- personal hygiene
- personal protective equipment needed, including practical instructions for its correct use and its limitations
- risk of dermal contact and inhalation exposure
- risk in relation to application process used
- skin and inhalation protection scheme
- ventilation
- cleaning, leakages, maintenance
- discarding empty packaging
- protection of bystanders
- identification of critical handling stages
- specific national code systems (if applicable)

- CONTINUED ON NEXT PAGE -

**406200001 - CATALIZADOR ESMALTE TKROM GLASS COMPONENTE B****SECTION 15: REGULATORY INFORMATION (continued)**

- behaviour-based safety
- certification or documented proof that training has been successfully completed
- (b) intermediate level training, including on-line training, on:
  - additional behaviour-based aspects
  - maintenance
  - management of change
  - evaluation of existing safety instructions
  - risk in relation to application process used
  - certification or documented proof that training has been successfully completed

(c) advanced training, including on-line training, on:

- any additional certification needed for the specific uses covered
- spraying outside a spraying booth
- open handling of hot or warm formulations (> 45 °C)
- certification or documented proof that training has been successfully completed

6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.

7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.

8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.

9. Member States shall include in their reports pursuant to Article 117(1) the following information:

- (a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law
- (b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates
- (c) national exposure limits for diisocyanates, if there are any
- (d) information about enforcement activities related to this restriction.

10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION****Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Precautionary statements

**Texts of the legislative phrases mentioned in section 2:**

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

H315: Causes skin irritation.

H412: Harmful to aquatic life with long lasting effects.

H373: May cause damage to organs through prolonged or repeated exposure (Oral). Organs affected: All gross lesions and masses.

H312+H332: Harmful in contact with skin or if inhaled.

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

- CONTINUED ON NEXT PAGE -



## 406200001 - CATALIZADOR ESMALTE TKROM GLASS COMPONENTE B

### SECTION 16: OTHER INFORMATION (continued)

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### CLP Regulation (EC) No 1272/2008:

Acute Tox. 1: H330 - Fatal if inhaled.

Acute Tox. 4: H302 - Harmful if swallowed.

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

#### Classification procedure:

Skin Sens. 1: Calculation method

STOT SE 3: Calculation method

Skin Irrit. 2: Calculation method

Aquatic Chronic 3: Calculation method

STOT RE 2: Calculation method

Acute Tox. 4: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

#### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

#### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -