



## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** 606030001 - BARNIZ TINTE MATE INCOLORO  
**Other means of identification:**  
**UFI:** YPD6-30FN-R00G-H5HG
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
 Relevant uses: Interior/exterior paint or lining for wood, metal, etc...  
 Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
 EUPINCA  
 C/ Londres, 13 - Pol. Ind. Cabezo Beaza  
 30353 Cartagena - Murcia - España  
 Phone: +34 968089000  
 info@grupotkrom.com  
 https://www.tkrom.com/
- 1.4 Emergency telephone number:** +34 968 08 90 00 (Oficce hours)

## SECTION 2: HAZARDS IDENTIFICATION \*\*

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
 Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
 Acute Tox. 4: Acute inhalation toxicity, Category 4, H332  
 Asp. Tox. 1: Aspiration hazard, Category 1, H304  
 Flam. Liq. 3: Flammable liquids, Category 3, H226  
 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**  
**CLP Regulation (EC) No 1272/2008:**  
 Danger
- 
- Hazard statements:**  
 Acute Tox. 4: H332 - Harmful if inhaled.  
 Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
 Flam. Liq. 3: H226 - Flammable liquid and vapour.  
 STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**  
 P101: If medical advice is needed, have product container or label at hand.  
 P102: Keep out of reach of children.  
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.  
 P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.  
 P501: Dispose of contents/container according to the separated collection system used in your municipality.
- Supplementary information:**  
 EUH066: Repeated exposure may cause skin dryness or cracking.
- Substances that contribute to the classification**  
 Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7; Reaction mass of ethylbenzene and m-xylene and p-xylene
- 2.3 Other hazards:**  
 Product does not meet PBT/vPvB criteria  
 Endocrine-disrupting properties: The product does not meet the criteria.

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

**Chemical description:** Mixture composed of additives, aggregates, colourants, pigments, plasticizers and resins in solvents

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 64742-48-9 EC: 265-150-3 Index: 649-327-00-6 REACH: 01-2119486659-16-XXXX	<b>Naphtha (petroleum), hydrotreated heavy, &lt; 0.1 % EC 200-753-7</b> <sup>1</sup>	ATP ATP01	25 - <50 %
Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger		
CAS: Non-applicable EC: 905-562-9 Index: Non-applicable REACH: 01-2119555267-33-XXXX	<b>Reaction mass of ethylbenzene and m-xylene and p-xylene</b> <sup>1</sup>	Self-classified	2,5 - <10 %
Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger		
CAS: 107-41-5 EC: 203-489-0 Index: 603-053-00-3 REACH: 01-2119539582-35-XXXX	<b>2-methylpentane-2,4-diol</b> <sup>1</sup>	Self-classified	<1 %
Regulation 1272/2008	Eye Irrit. 2: H319; Repr. 2: H361d; Skin Irrit. 2: H315 - Warning		
CAS: 112-34-5 EC: 203-961-6 Index: 603-096-00-8 REACH: 01-2119475104-44-XXXX	<b>2-(2-butoxyethoxy)ethanol</b> <sup>2</sup>	ATP CLP00	<1 %
Regulation 1272/2008	Eye Irrit. 2: H319 - Warning		
CAS: 67-56-1 EC: 200-659-6 Index: 603-001-00-X REACH: 01-2119433307-44-XXXX	<b>methanol</b> <sup>2</sup>	ATP CLP00	<1 %
Regulation 1272/2008	Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger		

<sup>1</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

<sup>2</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**Other information:**

Identification	Specific concentration limit
methanol CAS: 67-56-1 EC: 200-659-6	% (w/w) >=10: STOT SE 1 - H370 3<= % (w/w) <10: STOT SE 2 - H371

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
	LD50 oral	Non-applicable	
Reaction mass of ethylbenzene and m-xylene and p-xylene			
CAS: Non-applicable	LD50 dermal	1100 mg/kg (ATEi)	Rat
EC: 905-562-9	LC50 inhalation	11 mg/L (ATEi)	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

**SECTION 4: FIRST AID MEASURES (continued)**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media:****Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

**Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

It is recommended to avoid environmental spillage of both the product and its container.

**6.3 Methods and material for containment and cleaning up:**

- CONTINUED ON NEXT PAGE -



**SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	10 ppm	67,5 mg/m <sup>3</sup>
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	IOELV (STEL)	15 ppm	101,2 mg/m <sup>3</sup>
methanol CAS: 67-56-1 EC: 200-659-6	IOELV (8h)	200 ppm	260 mg/m <sup>3</sup>
	IOELV (STEL)		

**DNEL (Workers):**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1286,4 mg/m <sup>3</sup>	1066,67 mg/m <sup>3</sup>	Non-applicable	837,5 mg/m <sup>3</sup>
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
2-methylpentane-2,4-diol CAS: 107-41-5 EC: 203-489-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	42 mg/kg	Non-applicable
	Inhalation	Non-applicable	98 mg/m <sup>3</sup>	44,4 mg/m <sup>3</sup>	49 mg/m <sup>3</sup>
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	101,2 mg/m <sup>3</sup>	67,5 mg/m <sup>3</sup>	67,5 mg/m <sup>3</sup>
methanol CAS: 67-56-1 EC: 200-659-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	20 mg/kg	Non-applicable	20 mg/kg	Non-applicable
	Inhalation	130 mg/m <sup>3</sup>	130 mg/m <sup>3</sup>	130 mg/m <sup>3</sup>	130 mg/m <sup>3</sup>

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1152 mg/m <sup>3</sup>	640 mg/m <sup>3</sup>	Non-applicable	178,57 mg/m <sup>3</sup>
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
2-methylpentane-2,4-diol CAS: 107-41-5 EC: 203-489-0	Oral	Non-applicable	Non-applicable	1,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
	Inhalation	Non-applicable	49 mg/m <sup>3</sup>	7,8 mg/m <sup>3</sup>	25 mg/m <sup>3</sup>
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	50 mg/kg	Non-applicable
	Inhalation	Non-applicable	60,7 mg/m <sup>3</sup>	40,5 mg/m <sup>3</sup>	40,5 mg/m <sup>3</sup>
methanol CAS: 67-56-1 EC: 200-659-6	Oral	4 mg/kg	Non-applicable	4 mg/kg	Non-applicable
	Dermal	4 mg/kg	Non-applicable	4 mg/kg	Non-applicable
	Inhalation	26 mg/m <sup>3</sup>	26 mg/m <sup>3</sup>	26 mg/m <sup>3</sup>	26 mg/m <sup>3</sup>

**PNEC:**

Identification					
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	STP	6,58 mg/L	Fresh water	0,327 mg/L	
	Soil	2,31 mg/kg	Marine water	0,327 mg/L	
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg	
2-methylpentane-2,4-diol CAS: 107-41-5 EC: 203-489-0	STP	20 mg/L	Fresh water	0,429 mg/L	
	Soil	0,066 mg/kg	Marine water	0,043 mg/L	
	Intermittent	4,29 mg/L	Sediment (Fresh water)	1,59 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,159 mg/kg	
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	STP	200 mg/L	Fresh water	1,1 mg/L	
	Soil	0,32 mg/kg	Marine water	0,11 mg/L	
	Intermittent	11 mg/L	Sediment (Fresh water)	4,4 mg/kg	
	Oral	0,056 g/kg	Sediment (Marine water)	0,44 mg/kg	

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification				
methanol	STP	100 mg/L	Fresh water	20,8 mg/L
CAS: 67-56-1	Soil	100 mg/kg	Marine water	2,08 mg/L
EC: 200-659-6	Intermittent	1540 mg/L	Sediment (Fresh water)	77 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,7 mg/kg

**8.2 Exposure controls:**

**A.- Individual protection measures, such as personal protective equipment**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	<b>CE</b> CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	<b>CE</b> CAT III	EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	<b>CE</b> CAT II	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	<b>CE</b> CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	<b>CE</b> CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

- CONTINUED ON NEXT PAGE -



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	36,19 % weight
V.O.C. density at 20 °C:	377,26 kg/m <sup>3</sup> (377,26 g/L)
Average carbon number:	8,85
Average molecular weight:	127,3 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	379,59 kg/m <sup>3</sup> (379,59 g/L)
EU limit for the product (Cat. A.E):	400 g/L (2010)
Components:	Non-applicable

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Characteristic
Colour:	Colourless
Odour:	Not available
Odour threshold:	Non-applicable *

#### Volatility:

Boiling point at atmospheric pressure:	147 °C
Vapour pressure at 20 °C:	645 Pa
Vapour pressure at 50 °C:	3497,3 Pa (3,5 kPa)
Evaporation rate at 20 °C:	Non-applicable *

#### Product description:

Density at 20 °C:	1042,4 kg/m <sup>3</sup>
Relative density at 20 °C:	1,042
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	<20,5 mm <sup>2</sup> /s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

#### Flammability:

Flash Point:	24 °C
--------------	-------

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Flammability (solid, gas): Non-applicable \*  
 Autoignition temperature: 200 °C  
 Lower flammability limit: Not available  
 Upper flammability limit: Not available

**Particle characteristics:**

Median equivalent diameter: Non-applicable

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties: Non-applicable \*  
 Oxidising properties: Non-applicable \*  
 Corrosive to metals: Non-applicable \*  
 Heat of combustion: Non-applicable \*  
 Aerosols-total percentage (by mass) of flammable components: Non-applicable \*

**Other safety characteristics:**

Surface tension at 20 °C: Non-applicable \*  
 Refraction index: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health.

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- CONTINUED ON NEXT PAGE -





**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

**A- Ingestion (acute effect):**

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**B- Inhalation (acute effect):**

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

**C- Contact with the skin and the eyes (acute effect):**

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):**

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Reaction mass of ethylbenzene and m-xylene and p-xylene (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3); Talc (3); 2,6-di-tert-butyl-p-cresol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**E- Sensitizing effects:**

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**F- Specific target organ toxicity (STOT) - single exposure:**

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

**G- Specific target organ toxicity (STOT)-repeated exposure:**

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

**H- Aspiration hazard:**

The consumption of a considerable dose can cause pulmonary damage.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	Route	Dose	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (ATEi)	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	LD50 oral	15000 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
methanol CAS: 67-56-1 EC: 200-659-6	LD50 oral	100 mg/kg	
	LD50 dermal	300 mg/kg	
	LC50 inhalation	3 mg/L (4 h)	Rat

**11.2 Information on other hazards:**

- CONTINUED ON NEXT PAGE -



**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

**Endocrine disrupting properties**

Endocrine-disrupting properties: The product does not meet the criteria.

**Other information**

Non-applicable

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**12.1 Toxicity:**

**Acute toxicity:**

Identification	Concentration		Species	Genus
	LC50			
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	LC50	2200 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1000 mg/L (96 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	LC50	>10 - 100 mg/L (96 h)		Fish
	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae
2-methylpentane-2,4-diol CAS: 107-41-5 EC: 203-489-0	LC50	9910 mg/L (96 h)	Gambusia affinis	Fish
	EC50	5410 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	LC50	1300 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	2850 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	53 mg/L (192 h)	Microcystis aeruginosa	Algae
methanol CAS: 67-56-1 EC: 200-659-6	LC50	15400 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	12000 mg/L (96 h)	Nitrocras spinipes	Crustacean
	EC50	530 mg/L (168 h)	Microcystis aeruginosa	Algae

**Chronic toxicity:**

Identification	Concentration		Species	Genus
	NOEC			
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
methanol CAS: 67-56-1 EC: 200-659-6	NOEC	15800 mg/L	Oryzias latipes	Fish
	NOEC	122 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:**

**Substance-specific information:**

Identification	Degradability		Biodegradability	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	89,9 %
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
2-methylpentane-2,4-diol CAS: 107-41-5 EC: 203-489-0	BOD5	0 g O2/g	Concentration	100 mg/L
	COD	0,2 g O2/g	Period	14 days
	BOD5/COD	0,01	% Biodegradable	76,4 %
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	BOD5	0,25 g O2/g	Concentration	100 mg/L
	COD	2,08 g O2/g	Period	28 days
	BOD5/COD	0,12	% Biodegradable	92 %

- CONTINUED ON NEXT PAGE -



**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Degradability		Biodegradability	
	methanol CAS: 67-56-1 EC: 200-659-6	BOD5	Non-applicable	Concentration
	COD	1,42 g O2/g	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	92 %

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

Identification	Bioaccumulation potential	
	Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	BCF
	Pow Log	2.77
	Potential	Low
2-methylpentane-2,4-diol CAS: 107-41-5 EC: 203-489-0	BCF	
	Pow Log	0.14
	Potential	
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	BCF	0.46
	Pow Log	0.56
	Potential	Low
methanol CAS: 67-56-1 EC: 200-659-6	BCF	3
	Pow Log	-0.77
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
	Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Koc	100	Henry
	Conclusion	High	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
2-methylpentane-2,4-diol CAS: 107-41-5 EC: 203-489-0	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	1,577E-2 N/m (25 °C)	Moist soil	Non-applicable
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Koc	48	Henry	7,2E-9 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	No
	Surface tension	3,395E-2 N/m (25 °C)	Moist soil	No
methanol CAS: 67-56-1 EC: 200-659-6	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,355E-2 N/m (25 °C)	Moist soil	Non-applicable

**12.5 Results of PBT and vPvB assessment:**

Product does not meet PBT/vPvB criteria

**12.6 Endocrine disrupting properties:**

Endocrine-disrupting properties: The product does not meet the criteria.

**12.7 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

**Type of waste (Regulation (EU) No 1357/2014):**

- CONTINUED ON NEXT PAGE -



**SECTION 13: DISPOSAL CONSIDERATIONS (continued)**

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2023 and RID 2023:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Special regulations: 163, 367, 650  
Tunnel restriction code: D/E  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**  
Special regulations: 223, 955, 163, 367  
EmS Codes: F-E, S-E  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2023:



SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

SECTION 15: REGULATORY INFORMATION

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable  
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable  
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable  
Article 95, REGULATION (EU) No 528/2012: Non-applicable  
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Shall not be used in:  
—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,  
—tricks and jokes,  
—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.  
Laboral exposure to respirable crystalline silica must be controlled in accordance with Directive (EU) 2022/431, of the European Parliament and of the Council, of March 9, 2022, amending Directive 2004/37/EC, relating to the protection of workers against risks related to exposure to carcinogens or mutagens during work.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):  
· Precautionary statements

**Texts of the legislative phrases mentioned in section 2:**



## SECTION 16: OTHER INFORMATION (continued)

H336: May cause drowsiness or dizziness.  
 H332: Harmful if inhaled.  
 H304: May be fatal if swallowed and enters airways.  
 H226: Flammable liquid and vapour.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.  
 Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.  
 Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.  
 Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
 Eye Irrit. 2: H319 - Causes serious eye irritation.  
 Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  
 Flam. Liq. 3: H226 - Flammable liquid and vapour.  
 Repr. 2: H361d - Suspected of damaging the unborn child.  
 Skin Irrit. 2: H315 - Causes skin irritation.  
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).  
 STOT SE 1: H370 - Causes damage to organs.  
 STOT SE 3: H335 - May cause respiratory irritation.  
 STOT SE 3: H336 - May cause drowsiness or dizziness.

**Classification procedure:**

STOT SE 3: Calculation method  
 Acute Tox. 4: Calculation method  
 Asp. Tox. 1: Calculation method  
 Flam. Liq. 3: Calculation method (2.6.4.3)

**Advice related to training:**

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
 IMDG: International maritime dangerous goods code  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organisation  
 COD: Chemical Oxygen Demand  
 BOD5: 5day biochemical oxygen demand  
 BCF: Bioconcentration factor  
 LD50: Lethal Dose 50  
 LC50: Lethal Concentration 50  
 EC50: Effective concentration 50  
 LogPOW: Octanolwater partition coefficient  
 Koc: Partition coefficient of organic carbon  
 UFI: unique formula identifier  
 IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -