

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** 812000001 - DISOLVENTE 370 EPOXI ESTUFA
Other means of identification:
UFI: 3X78-P0UF-100J-QV6H
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses (Consumer use): Thinner for the application of paints and varnishes
Relevant uses (Professional users): Thinner for the application of paints and varnishes
Relevant uses (Industrial user): Thinner for the application of paints and varnishes
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
EUPINCA
C/ Londres, 13 - Pol. Ind. Cabezo Beaza
30353 Cartagena - Murcia - España
Phone: +34 968089000
info@grupotkrom.com
<https://www.tkrom.com/>
- 1.4 Emergency telephone number:** +34 968 08 90 00 (Oficce hours)

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Eye Irrit. 2: Eye irritation, Category 2, H319
Flam. Liq. 2: Flammable liquids, Category 2, H225
Repr. 2: Reproductive toxicity, Category 2, H361
Skin Irrit. 2: Skin irritation, Category 2, H315
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2, H373
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Danger

Hazard statements:
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Repr. 2: H361 - Suspected of damaging fertility or the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral). Organs affected: All gross lesions and masses.
STOT SE 3: H336 - May cause drowsiness or dizziness.
STOT SE 3: H335 - May cause respiratory irritation.
Precautionary statements:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 2: HAZARDS IDENTIFICATION ** (continued)

P101: If medical advice is needed, have product container or label at hand.
 P102: Keep out of reach of children.
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P264: Wash thoroughly after handling.
 P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
 P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501: Dispose of contents/container according to the separated collection system used in your municipality.

Substances that contribute to the classification

Toluene; Reaction mass of ethylbenzene and m-xylene and p-xylene; Butanone; 4-hydroxy-4-methylpentan-2-one

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Not relevant

3.2 Mixture:

Chemical description: Solvent/s

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | | Concentration |
|---|--|---|----------------------|
| CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51-XXXX | Toluene⁽¹⁾ ATP CLP00 | | 25 - <50 % |
| | Regulation 1272/2008 | Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger | |
| CAS: Not relevant EC: 905-562-9 Index: Not relevant REACH: 01-2119555267-33-XXXX | Reaction mass of ethylbenzene and m-xylene and p-xylene⁽¹⁾ Self-classified | | 25 - <50 % |
| | Regulation 1272/2008 | Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger | |
| CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43-XXXX | Butanone⁽¹⁾ ATP CLP00 | | 10 - <25 % |
| | Regulation 1272/2008 | Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger | |
| CAS: 123-42-2 EC: 204-626-7 Index: 603-016-00-1 REACH: 01-2119473975-21-XXXX | 4-hydroxy-4-methylpentan-2-one⁽¹⁾ Self-classified | | 10 - <25 % |
| | Regulation 1272/2008 | Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361; STOT SE 3: H335 - Warning | |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

| Identification | Specific concentration limit |
|--|-----------------------------------|
| 4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7 | % (w/w) >=10: Eye Irrit. 2 - H319 |

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

| Identification | Acute toxicity | | Genus |
|---|------------------------|--------------|-------|
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9 | LD50 oral | Not relevant | |
| | LD50 dermal | 1100 mg/kg | Rat |
| | LC50 inhalation vapour | 11 mg/L | |

- CONTINUED ON NEXT PAGE -

**SECTION 4: FIRST AID MEASURES****4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

- CONTINUED ON NEXT PAGE -

**SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification | Occupational exposure limits | | |
|--|------------------------------|---------|-----------------------|
| Toluene ⁽¹⁾ CAS: 108-88-3 EC: 203-625-9 | IOELV (8h) | 50 ppm | 192 mg/m ³ |
| | IOELV (STEL) | 100 ppm | 384 mg/m ³ |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9 | IOELV (8h) | 50 ppm | 221 mg/m ³ |
| | IOELV (STEL) | 100 ppm | 442 mg/m ³ |
| Butanone CAS: 78-93-3 EC: 201-159-0 | IOELV (8h) | 200 ppm | 600 mg/m ³ |
| | IOELV (STEL) | 300 ppm | 900 mg/m ³ |

⁽¹⁾ Skin

DNEL (Workers):

| Identification | | Short exposure | | Long exposure | |
|---|------------|-----------------------|-----------------------|------------------------|-----------------------|
| | | Systemic | Local | Systemic | Local |
| Toluene CAS: 108-88-3 EC: 203-625-9 | Oral | Not relevant | Not relevant | Not relevant | Not relevant |
| | Dermal | Not relevant | Not relevant | 384 mg/kg | Not relevant |
| | Inhalation | 384 mg/m ³ | 384 mg/m ³ | 192 mg/m ³ | 192 mg/m ³ |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9 | Oral | Not relevant | Not relevant | Not relevant | Not relevant |
| | Dermal | Not relevant | Not relevant | 212 mg/kg | Not relevant |
| | Inhalation | 442 mg/m ³ | 442 mg/m ³ | 221 mg/m ³ | 221 mg/m ³ |
| Butanone CAS: 78-93-3 EC: 201-159-0 | Oral | Not relevant | Not relevant | Not relevant | Not relevant |
| | Dermal | Not relevant | Not relevant | 1161 mg/kg | Not relevant |
| | Inhalation | Not relevant | Not relevant | 600 mg/m ³ | Not relevant |
| 4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7 | Oral | Not relevant | Not relevant | Not relevant | Not relevant |
| | Dermal | Not relevant | Not relevant | 467 mg/kg | Not relevant |
| | Inhalation | Not relevant | 240 mg/m ³ | 32,6 mg/m ³ | Not relevant |

DNEL (General population):

| Identification | | Short exposure | | Long exposure | |
|---|------------|-----------------------|-----------------------|------------------------|------------------------|
| | | Systemic | Local | Systemic | Local |
| Toluene CAS: 108-88-3 EC: 203-625-9 | Oral | Not relevant | Not relevant | 8,13 mg/kg | Not relevant |
| | Dermal | Not relevant | Not relevant | 226 mg/kg | Not relevant |
| | Inhalation | 226 mg/m ³ | 226 mg/m ³ | 56,5 mg/m ³ | 56,5 mg/m ³ |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9 | Oral | Not relevant | Not relevant | 12,5 mg/kg | Not relevant |
| | Dermal | Not relevant | Not relevant | 125 mg/kg | Not relevant |
| | Inhalation | 260 mg/m ³ | 260 mg/m ³ | 65,3 mg/m ³ | 65,3 mg/m ³ |
| Butanone CAS: 78-93-3 EC: 201-159-0 | Oral | Not relevant | Not relevant | 31 mg/kg | Not relevant |
| | Dermal | Not relevant | Not relevant | 412 mg/kg | Not relevant |
| | Inhalation | Not relevant | Not relevant | 106 mg/m ³ | Not relevant |
| 4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7 | Oral | Not relevant | Not relevant | 1,67 mg/kg | Not relevant |
| | Dermal | Not relevant | Not relevant | 33 mg/kg | Not relevant |
| | Inhalation | Not relevant | Not relevant | 5,8 mg/m ³ | Not relevant |

PNEC:

| Identification | | | | | |
|---|--------------|--------------|-------------------------|--|-------------|
| Toluene CAS: 108-88-3 EC: 203-625-9 | STP | 13,61 mg/L | Fresh water | | 0,68 mg/L |
| | Soil | 2,89 mg/kg | Marine water | | 0,68 mg/L |
| | Intermittent | 0,68 mg/L | Sediment (Fresh water) | | 16,39 mg/kg |
| | Oral | Not relevant | Sediment (Marine water) | | 16,39 mg/kg |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9 | STP | 6,58 mg/L | Fresh water | | 0,327 mg/L |
| | Soil | 2,31 mg/kg | Marine water | | 0,327 mg/L |
| | Intermittent | 0,327 mg/L | Sediment (Fresh water) | | 12,46 mg/kg |
| | Oral | Not relevant | Sediment (Marine water) | | 12,46 mg/kg |

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Identification | | | | |
|--|--------------|--------------|-------------------------|--------------|
| Butanone CAS: 78-93-3 EC: 201-159-0 | STP | 709 mg/L | Fresh water | 55,8 mg/L |
| | Soil | 22,5 mg/kg | Marine water | 55,8 mg/L |
| | Intermittent | 55,8 mg/L | Sediment (Fresh water) | 284,74 mg/kg |
| | Oral | 1 g/kg | Sediment (Marine water) | 284,7 mg/kg |
| 4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7 | STP | 100 mg/L | Fresh water | 2 mg/L |
| | Soil | 0,3 mg/kg | Marine water | 0,2 mg/L |
| | Intermittent | 1 mg/L | Sediment (Fresh water) | 7,4 mg/kg |
| | Oral | Not relevant | Sediment (Marine water) | 0,74 mg/kg |

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|--|-------------|---------------------|--|
| Mandatory respiratory tract protection | Filter mask for gases and vapours (Filter type: A) | CAT III | EN 405:2002+A1:2010 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

C.- Specific protection for the hands

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-------------------------------|---|-------------|-------------------|--|
| Mandatory hand protection | Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm) | CAT III | EN ISO 21420:2020 | Replace the gloves at any sign of deterioration. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-------------------------------|-------------|------------|---|---|
| Mandatory face protection | Face shield | CAT II | EN 166:2002 UNE-EN ISO 18526-1 al 4:2020 UNE-EN ISO 18526-1 al 4:2020 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|-------------|---|---|
| Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties | CAT III | EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2005/A1:2011 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1995 | For professional use only. Clean periodically according to the manufacturer's instructions. |
| Mandatory foot protection | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties | CAT III | EN ISO 13287:2020 EN ISO 20345:2022 EN 13832-1:2019 | Replace boots at any sign of deterioration. |



F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

| Emergency measure | Standards | Emergency measure | Standards |
|---|---|--|--|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

| | |
|---------------------------|---------------------------------------|
| V.O.C. (Supply): | 100 % weight |
| V.O.C. density at 20 °C: | 868,02 kg/m ³ (868,02 g/L) |
| Average carbon number: | 6,5 |
| Average molecular weight: | 97,13 g/mol |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

| | |
|--------------------------|----------------|
| Physical state at 20 °C: | Liquid |
| Appearance: | Viscous |
| Colour: | Colourless |
| Odour: | Not relevant * |
| Odour threshold: | Not relevant * |

Volatility:

| | |
|--|-------------------------|
| Boiling point at atmospheric pressure: | 116 °C |
| Vapour pressure at 20 °C: | 3669 Pa |
| Vapour pressure at 50 °C: | 14363,08 Pa (14,36 kPa) |
| Evaporation rate at 20 °C: | Not relevant * |

Product description:

| | |
|--|--------------------------|
| Density at 20 °C: | 868 kg/m ³ |
| Relative density at 20 °C: | 0,868 |
| Dynamic viscosity at 20 °C: | 0,72 mPa·s |
| Kinematic viscosity at 20 °C: | 0,83 mm ² /s |
| Kinematic viscosity at 40 °C: | >20,5 mm ² /s |
| Concentration: | Not relevant * |
| pH: | Not relevant * |
| Vapour density at 20 °C: | Not relevant * |
| Partition coefficient n-octanol/water 20 °C: | Not relevant * |
| Solubility in water at 20 °C: | Not relevant * |
| Solubility properties: | Not relevant * |
| Decomposition temperature: | Not relevant * |
| Melting point/freezing point: | Not relevant * |

Flammability:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

| | |
|----------------------------------|----------------|
| Flash Point: | 13 °C |
| Flammability (solid, gas): | Not relevant * |
| Autoignition temperature: | 465 °C |
| Lower flammability limit: | Not relevant * |
| Upper flammability limit: | Not relevant * |
| Particle characteristics: | |
| Median equivalent diameter: | Not relevant * |

9.2 Other information:

Information with regard to physical hazard classes:

| | |
|--|----------------|
| Explosive properties: | Not relevant * |
| Oxidising properties: | Not relevant * |
| Corrosive to metals: | Not relevant * |
| Heat of combustion: | Not relevant * |
| Aerosols-total percentage (by mass) of flammable components: | Not relevant * |

Other safety characteristics:

| | |
|---------------------------|----------------|
| Surface tension at 20 °C: | Not relevant * |
| Refraction index: | Not relevant * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Toluene (3); Reaction mass of ethylbenzene and m-xylene and p-xylene (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Suspected of damaging fertility or the unborn child
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness. Organs affected: All gross lesions and masses.
 - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|---|------------------------|-----------------|--------|
| Toluene CAS: 108-88-3 EC: 203-625-9 | LD50 oral | 5580 mg/kg | Rat |
| | LD50 dermal | 12124 mg/kg | Rat |
| | LC50 inhalation vapour | 28,1 mg/L (4 h) | Rat |
| Butanone CAS: 78-93-3 EC: 201-159-0 | LD50 oral | 4000 mg/kg | Rat |
| | LD50 dermal | 6400 mg/kg | Rabbit |
| | LC50 inhalation vapour | 23,5 mg/L (4 h) | Rat |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9 | LD50 oral | 2100 mg/kg | Rat |
| | LD50 dermal | 1100 mg/kg | Rat |
| | LC50 inhalation gases | 4500 mg/L | |
| | LC50 inhalation vapour | 11 mg/L | |
| | LC50 inhalation dust | 1,5 mg/L | |
| | LC50 inhalation mist | 1,5 mg/L | |

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

| Identification | Acute toxicity | | Genus |
|--|-----------------|------------|-------|
| 4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7 | LD50 oral | 3002 mg/kg | Rat |
| | LD50 dermal | | |
| | LC50 inhalation | | |

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

| Identification | Concentration | | Species | Genus |
|---|---------------|-----------------------|---------------------------------|------------|
| Toluene CAS: 108-88-3 EC: 203-625-9 | LC50 | 5,5 mg/L (96 h) | Oncorhynchus kisutch | Fish |
| | EC50 | 3,78 mg/L (48 h) | Ceriodaphnia dubia | Crustacean |
| | EC50 | Not relevant | | |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9 | LC50 | >10 - 100 mg/L (96 h) | | Fish |
| | EC50 | >10 - 100 mg/L (48 h) | | Crustacean |
| | EC50 | >10 - 100 mg/L (72 h) | | Algae |
| Butanone CAS: 78-93-3 EC: 201-159-0 | LC50 | 3220 mg/L (96 h) | Pimephales promelas | Fish |
| | EC50 | 5091 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | 4300 mg/L (168 h) | Scenedesmus quadricauda | Algae |
| 4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7 | LC50 | 110 mg/L (96 h) | Oryzias latipes | Fish |
| | EC50 | 1000 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | 1000 mg/L (72 h) | Pseudokirchneriella subcapitata | Algae |

Chronic toxicity:

| Identification | Concentration | | Species | Genus |
|--|---------------|--------------|---------------------|------------|
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9 | NOEC | 1,3 mg/L | Oncorhynchus mykiss | Fish |
| | NOEC | 1,17 mg/L | Ceriodaphnia dubia | Crustacean |
| 4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7 | NOEC | Not relevant | | |
| | NOEC | 100 mg/L | Daphnia magna | Crustacean |

12.2 Persistence and degradability:

Substance-specific information:

| Identification | Degradability | | Biodegradability | |
|---|---------------|--------------|------------------|--------------|
| Toluene CAS: 108-88-3 EC: 203-625-9 | BOD5 | 2,5 g O2/g | Concentration | 100 mg/L |
| | COD | Not relevant | Period | 14 days |
| | BOD5/COD | Not relevant | % Biodegradable | 100 % |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Not relevant EC: 905-562-9 | BOD5 | Not relevant | Concentration | Not relevant |
| | COD | Not relevant | Period | 28 days |
| | BOD5/COD | Not relevant | % Biodegradable | 88 % |
| Butanone CAS: 78-93-3 EC: 201-159-0 | BOD5 | 2,03 g O2/g | Concentration | Not relevant |
| | COD | 2,31 g O2/g | Period | 20 days |
| | BOD5/COD | 0,88 | % Biodegradable | 89 % |
| 4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7 | BOD5 | Not relevant | Concentration | 57.5 mg/L |
| | COD | Not relevant | Period | 28 days |
| | BOD5/COD | Not relevant | % Biodegradable | 98,51 % |

12.3 Bioaccumulative potential:

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

Substance-specific information:

| Identification | Bioaccumulation potential | |
|---|---------------------------|----------|
| Toluene | BCF | 90 |
| CAS: 108-88-3 | Pow Log | 2.73 |
| EC: 203-625-9 | Potential | Moderate |
| Reaction mass of ethylbenzene and m-xylene and p-xylene | BCF | 9 |
| CAS: Not relevant | Pow Log | 2.77 |
| EC: 905-562-9 | Potential | Low |
| Butanone | BCF | 3 |
| CAS: 78-93-3 | Pow Log | 0.29 |
| EC: 201-159-0 | Potential | Low |
| 4-hydroxy-4-methylpentan-2-one | BCF | 0.5 |
| CAS: 123-42-2 | Pow Log | |
| EC: 204-626-7 | Potential | Low |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|---|-----------------------|----------------------|------------|-------------------------------|
| Toluene | Koc | 178 | Henry | 672,8 Pa·m ³ /mol |
| CAS: 108-88-3 | Conclusion | Moderate | Dry soil | Yes |
| EC: 203-625-9 | Surface tension | 2,793E-2 N/m (25 °C) | Moist soil | Yes |
| Reaction mass of ethylbenzene and m-xylene and p-xylene | Koc | 202 | Henry | 524,86 Pa·m ³ /mol |
| CAS: Not relevant | Conclusion | Moderate | Dry soil | Yes |
| EC: 905-562-9 | Surface tension | Not relevant | Moist soil | Yes |
| Butanone | Koc | 30 | Henry | 5,77 Pa·m ³ /mol |
| CAS: 78-93-3 | Conclusion | Very High | Dry soil | Yes |
| EC: 201-159-0 | Surface tension | 2,396E-2 N/m (25 °C) | Moist soil | Yes |
| 4-hydroxy-4-methylpentan-2-one | Koc | 1 | Henry | Not relevant |
| CAS: 123-42-2 | Conclusion | Very High | Dry soil | Not relevant |
| EC: 204-626-7 | Surface tension | 2,963E-2 N/m (25 °C) | Moist soil | Not relevant |

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---|--|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | Hazardous |

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

- CONTINUED ON NEXT PAGE -



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



- | | |
|--|------------------------|
| 14.1 UN number or ID number: | UN1263 |
| 14.2 UN proper shipping name: | PAINT RELATED MATERIAL |
| 14.3 Transport hazard class(es): | 3 |
| Labels: | 3 |
| 14.4 Packing group: | II |
| 14.5 Environmental hazards: | No |
| 14.6 Special precautions for user | |
| Special regulations: | 163, 367, 640D, 650 |
| Tunnel restriction code: | D/E |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 5 L |
| 14.7 Maritime transport in bulk according to IMO instruments: | Not relevant |

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



- | | |
|--|------------------------|
| 14.1 UN number or ID number: | UN1263 |
| 14.2 UN proper shipping name: | PAINT RELATED MATERIAL |
| 14.3 Transport hazard class(es): | 3 |
| Labels: | 3 |
| 14.4 Packing group: | II |
| 14.5 Marine pollutant: | No |
| 14.6 Special precautions for user | |
| Special regulations: | 163, 367 |
| EmS Codes: | F-E, S-E |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 5 L |
| Segregation group: | Not relevant |
| 14.7 Maritime transport in bulk according to IMO instruments: | Not relevant |

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



- | | |
|--|------------------------|
| 14.1 UN number or ID number: | UN1263 |
| 14.2 UN proper shipping name: | PAINT RELATED MATERIAL |
| 14.3 Transport hazard class(es): | 3 |
| Labels: | 3 |
| 14.4 Packing group: | II |
| 14.5 Environmental hazards: | No |
| 14.6 Special precautions for user | |
| Physico-Chemical properties: | see section 9 |
| 14.7 Maritime transport in bulk according to IMO instruments: | Not relevant |

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- CONTINUED ON NEXT PAGE -



SECTION 15: REGULATORY INFORMATION (continued)

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

| Section | Description | Lower-tier requirements | Upper-tier requirements |
|---------|-------------------|-------------------------|-------------------------|
| P5c | FLAMMABLE LIQUIDS | 5000 | 50000 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Hazard statements

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or repeated exposure.

H361: Suspected of damaging fertility or the unborn child.

H412: Harmful to aquatic life with long lasting effects.

H373: May cause damage to organs through prolonged or repeated exposure (Oral). Organs affected: All gross lesions and masses.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:



SECTION 16: OTHER INFORMATION ** (continued)

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.
 Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
 Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
 Eye Irrit. 2: H319 - Causes serious eye irritation.
 Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
 Flam. Liq. 3: H226 - Flammable liquid and vapour.
 Repr. 2: H361 - Suspected of damaging fertility or the unborn child.
 Repr. 2: H361d - Suspected of damaging the unborn child.
 Skin Irrit. 2: H315 - Causes skin irritation.
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
 STOT SE 3: H335 - May cause respiratory irritation.
 STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Skin Irrit. 2: Calculation method
 STOT SE 3: Calculation method
 STOT SE 3: Calculation method
 STOT RE 2: Calculation method
 Repr. 2: Calculation method
 Aquatic Chronic 3: Calculation method
 STOT RE 2: Calculation method
 Flam. Liq. 2: Calculation method (2.6.4.3)
 Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
 IMDG: International maritime dangerous goods code
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organisation
 COD: Chemical Oxygen Demand
 BOD5: 5day biochemical oxygen demand
 BCF: Bioconcentration factor
 LD50: Lethal Dose 50
 LC50: Lethal Concentration 50
 EC50: Effective concentration 50
 LogPOW: Octanolwater partition coefficient
 Koc: Partition coefficient of organic carbon
 UFI: unique formula identifier
 IARC: International Agency for Research on Cancer

*** Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -