



BLOCK STAIN

SALES FORMAT

4L, 750ml

DESCRIPTION

A matte acrylic paint designed to cover stains which, thanks to the technology used in its formulation, acts effectively as a barrier against all types of stains, including damp, smoke, nicotine and grease, amongst others.

SCOPE OF APPLICATION

Indoor
Building materials
Cement, Concrete
Bedrooms, Kitchens, Bathrooms
Garages, Basements
Wineries

PROPERTIES

- Excellent coverage
- Very fast drying
- High insulating power
- Excellent adhesion
- Good whiteness
- Can be repainted with acrylic paints
- Matt finish
- Easy to apply

TECHNICAL DATA

Chemical composition	Acrylic resins	
Colour	White	
Finish	Matte	UNE-EN ISO 2813
Gloss 85°	10 ± 2	UNE-EN ISO 2813
Density	1.61 ± 0.05 g/ml	UNE-EN ISO 2811-1
Viscosity	100 ± 10 KU	UNE 48076
Volume solids	53 ± 2%	UNE-EN ISO 23811
VOC	< 500 g/L. Maximum value permitted by the EU: 500 g/L	2004/42/II Category (i)
Theoretical coverage	10–12 m ² /L – 5–7 m ² /kg (50 dry microns)	
Drying times	Touch-dry: 5–10 mins / Fully dry: 2 hours	
Recoating time	from 1 hour	
Dilution	0–10% depending on the application method	
Diluents	TKROM SOL. 376 ANTIOXIDANT or SOL. 350 CHLORO-RUBBER	
Cleaning	TKROM DISOLVENTE UNIVERSAL 302	

The technical data specified may vary if the material is tinted.

PREPARATION OF THE SUBSTRATE

NEW SURFACES

On new, solid, clean and dry surfaces, no surface preparation is required; apply TKROM BLOCKSTAIN directly.

ALREADY PAINTED SURFACES

On previously painted surfaces, if the paint is in good condition, apply the product directly. For paint in poor condition, remove any poorly adhered or defective areas, as well as dust, grease and dirt. If mould is present, mechanically clean the area affected by microorganisms using scrapers, brushes, scourers, etc., to remove the microorganisms, then apply TKROM LIMPIADOR REFORZANTE, allow to dry and apply TKROM BLOCKSTAIN.

APPLICATION CONDITIONS

Substrate temperature	Min. + 5°C / Max. + 35°C
Ambient temperature	5°C / 35°C
Dew Point	The substrate temperature must be at least 3°C above the dew point to reduce the risk of flaking or efflorescence.

APPLICATION SYSTEM

System	Product	Yield	Dilution	Coats
PRIMING	TKROM BLOCKSTAIN	10-12 m ² /L - 5-7 m ² /kg (50 dry microns)	0-10% TKROM SOL. 376 ANTIOXIDANT or SOL. 350 CHLORO-RUBBER	1 or 2

APPLICATION RECOMMENDATIONS

Product preparation:	Stir until the product is thoroughly homogenised. Stir again periodically. Adjust the viscosity. During lengthy processes, evaporation will occur; readjust the viscosity.
Application method:	Can be applied with a brush or roller. Apply the product evenly to ensure stains are completely concealed and a uniform finish is achieved.

ADDITIONAL INFORMATION

Health and safety	Highly flammable. For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject. WASTE: HAZARDOUS. LER CODE: 080111
Storage	The product will remain stable in its original, unopened packaging at ambient temperatures not exceeding 30 °C or falling below 5 °C for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed, undamaged packaging, protected from frost and direct sunlight.
Tariff heading	TARIC code: 3208 20 90
Note	The technical information contained in this document is provided in good faith, based on laboratory tests and practical experience under normal conditions. However, the data may vary, particularly when the material is tinted or when using intense colours, in which case parameters such as density or solids by volume may be affected without compromising the product's performance. Users are advised to verify the suitability of the product for their specific application and to request the relevant colour safety data sheet from their distributor for reference.