



WOODMARK LASUR DISOLVENTE

SALES FORMAT

4L, 750ml



WoodMark
garantía
tkrom

DESCRIPTION

A solvent-based, penetrating wood stain, formulated with alkyd resins, which protects, preserves and enhances the appearance of timber both indoors and outdoors. A highly penetrating, microporous product that is weather- and UV-resistant, providing the timber with a high level of protection, acting as an open-pore finish and allowing the wood to breathe and maintain a balance between the moisture content of the substrate and that of the surrounding environment, whilst preserving the natural appearance of its grain as much as possible. WOODMARK Lasur Finish is elastic, so it adapts to the natural movements of the wood without cracking.

SCOPE OF APPLICATION

Outdoors/Indoor
Solid timber and plywood
Doors and windows
Beams
Key features
Pergolas
Garden furniture
Wooden surfaces

PROPERTIES

- High elasticity
- Microporous
- Fast-drying
- Outdoors/Indoor
- Ready to use
- Satin and Matte finishes
- Periodic application without stripping

TECHNICAL DATA

Chemical composition	Alkyd resins	
Colour	Colour chart	
Finish	Satin and Matte	
Density	0.90 ± 0.05 g/ml	UNE-EN ISO 2811-1
Viscosity	40 ± 60 sec (Ford No. 4)	ASTM D1200
Volume solids	25±2% (Satin)	UNE-EN ISO 23811
Volume solids	31±2% (Matte)	UNE-EN ISO 23811
Satin finish 60°/85°	35–50 / 55–70	UNE-EN ISO 2813
Gloss: Matte 60°/85°	<5 / <10	UNE-EN ISO 2813
VOC	< 600 g/L. Maximum value permitted by the EU: 700 g/L	2004/42/II A classification (f)
Theoretical coverage	12–13 m ² /L (20 dry microns)	
Drying times	Touch-dry: 4–6 hours	
Recoating time	24 hours	
Dilution	< 5%	
Thinner	TKROM DISOLVENTE SINTETICOS Y GRASOS 345	
Cleaning	TKROM DISOLVENTE SINTETICOS 345 SYNTHETIC AND OIL-BASED	

The technical data specified may vary if the material is tinted.

PREPARATION OF THE SUBSTRATE

GENERAL INFORMATION

Outdoors, do not apply if rain is forecast, in direct midday sun or on damp days.

UNPAINTED, UNDAMAGED WOODEN SURFACES

Lightly dry-sand the surface to remove any raised fibres. Apply two coats of W. WATER-BASED INSECTICIDAL PRIMER to ensure effective protection against rot-causing fungi and to improve the adhesion of the topcoats. Do not dilute or mix with other products; WOODMARK SOLVENT-BASED WOOD STAIN is supplied ready for direct application. Shake well before and during application until completely homogenised. Apply two coats of WOODMARK SOLVENT-BASED WOOD STAIN. It is recommended that the topcoats be applied within one month of applying the primer, although a later application does not reduce the primer's protective effect. It is recommended that the primer be applied before the timber is installed on site.

PAINTED WOODEN SURFACES

Completely remove old coats of paint or varnish by sanding or stripping. Proceed as described for unpainted surfaces.

WOOD SURFACES TREATED WITH WOOD STAIN (MAINTENANCE)

Clean and proceed as described for new surfaces. No prior stripping or sanding is required.

APPLICATION CONDITIONS

Substrate temperature	Min. + 5°C / Max. + 35°C
Ambient temperature	Min. + 5°C / Max. + 35°C
Substrate / ambient moisture	< 10% / < 80%
Dew Point	The substrate temperature must be at least 3°C above the dew point to reduce the risk of flaking or efflorescence.

APPLICATION SYSTEM

System	Product	Yield	Dilution	Coats
PRIMER	WOODMARK WATER-BASED INSECTICIDAL PRIMER	4-6 m ² /L (200 mL/m ²)	N/A	1 or 2
FINISH	WOODMARK SOLVENT-BASED WOOD STAIN	12-13 m ² /L (20 dry microns)	TKROM DISOLVENTE SINTETICOS GRASOS 345	1 or 2

APPLICATION RECOMMENDATIONS

Product preparation:	Do not dilute or mix with other products; the product is ready for use. Shake well before and during application.
Application method:	WOODMARK SOLVENT-BASED WOOD STAIN can be applied with a brush. Always apply to clean, dry surfaces that are free from grease and dust, and free from any varnish, paint or wax. Apply two coats of the product, following the grain of the wood, allowing 24 hours between coats. On surfaces exposed to harsh weather conditions, a third coat is recommended. Clear finishes are intended for use in indoor environments.

ADDITIONAL INFORMATION**Health and safety**

For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject. WASTE: HAZARDOUS. LER CODE: 080111

Storage

The product will remain stable in its original, unopened packaging at ambient temperatures not exceeding 30 °C or falling below 5 °C for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed, undamaged packaging, protected from frost and direct sunlight.

Tariff heading

TARIC code: 3208 90 91

Note

The technical information contained in this document is provided in good faith, based on laboratory tests and practical experience under normal conditions. However, the data may vary, particularly when the material is tinted or when using intense colours, in which case parameters such as density or solids by volume may be affected without compromising the product's performance. Users are advised to verify the suitability of the product for their specific application and to request the relevant colour safety data sheet from their distributor for reference.