

TINTE UNIVERSAL



SALES FORMAT

500ml, 50ml

DESCRIPTION

Concentrated liquid colourant for tinting water-based and solvent-based paints. Its lightfastness and colouring power depend on the pigment, as well as the quality and pigment-binding capacity of the paint.

SCOPE OF APPLICATION

For tinting water-based or solvent-based paints, such as synthetic enamels, oil-based paints, acrylic paints, distemper, glue-based paints, lime-based paints and cement-based paints.

PROPERTIES

- Fully compatible with most water-based and solvent-based paints
- Very easy to incorporate
- High tinting strength
- Solid, crisp colours
- High concentration and tinting strength

TECHNICAL DATA

Appearance	Liquid	
Colour	Letter	
Density	0.95–1.75 g/ml depending on colour	ISO 2811-1

APPLICATION PROCESS

Application

Stir until the product is thoroughly mixed. Outdoors, ensure that the chosen colour is lightfast. Do not use colourants with poor lightfastness. Suitable base products must be used and it is advisable to avoid pastel shades derived from the following tints: 794 Light Yellow; 795 Medium Yellow; 790 Vermilion. Add the required amount of TKROM UNIVERSAL TINT until the desired shade is achieved, without exceeding the 5% limit (depending on the colour) of the total paint volume. Thoroughly homogenise the mixture of paint and tint using mechanical means. Follow the application instructions in the technical data sheet for the paint used in the tinting process. Tools used must be cleaned immediately after use with water or any of the solvents recommended for diluting the product.

ADDITIONAL INFORMATION

Health and safety

For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject. WASTE: NON-HAZARDOUS. LER: 080112

Storage

The product will remain stable in its original, unopened packaging at ambient temperatures not exceeding 30°C or falling below 5°C for 12 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed and undamaged packaging, and protected from frost and direct sunlight.

Tariff heading

TARIC code: 3212 90 00

Note

The technical information contained in this document is provided in good faith, based on laboratory tests and practical experience under normal conditions. However, the data may vary, particularly when the material is tinted or when using intense colours, where parameters such as density or solids by volume may be affected without compromising the product's performance. Users are advised to verify the suitability of the product for their specific application and to request the relevant colour safety data sheet from their distributor for consultation.

