



# DISOLVENTE PARA PINTURA ANTICALÓRICA

## SALES FORMAT

25L

### DESCRIPTION

Solvent specially designed for diluting TKROM Anticalórica 400 C

### SCOPE OF APPLICATION

Specifically for the dilution of heat-resistant paints.

Tool cleaning.

Application viscosity regulator

### PROPERTIES

- High dilution and cleaning power
- Formulated with a balanced blend of solvents
- Average evaporation rate
- Facilitates levelling

### TECHNICAL DATA

CLASSIFICATION		
APPEARANCE	Liquid	
COLOUR	Colourless Transparent	
COLOUR	Characteristics	
DENSITY	0.87 ± 0.03 g/ml	ISO 2811-1

### APPLICATION PROCESS

#### Application

To adjust the application viscosity. Add to the varnish or paint in the proportion indicated in the product technical data sheet. Stir the mixture by hand or using mechanical means (but slowly) until a completely homogeneous product is achieved.

### ADDITIONAL INFORMATION

#### Health and safety

For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject.

WASTE: HAZARDOUS. LER: 080111

#### Storage

The product will remain stable in its original, unopened packaging at ambient temperatures not exceeding 30°C or falling below 5°C for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed and undamaged packaging, and protected from frost and direct sunlight.

#### Tariff heading

TARIC code: 3814 00 10

#### Note

The data provided in this technical data sheet may be subject to change depending on possible variations in formulation and, in any case, represent indicative values which do not exempt the user from carrying out the necessary tests to ensure the product is suitable for a specific application.