



DISOLVENTE 355 SINTEX SIN OLOR

SALES FORMAT

25L, 5L, 1L, 500ml

DESCRIPTION

Aromatic-free, low-odour isoparaffinic solvent, particularly suitable for all types of synthetic and oil-based enamels and paints, for application by brush, roller or spray gun.

SCOPE OF APPLICATION

Specifically for thinning synthetic and oil-based paints. For cleaning tools with products where recommended. Application viscosity regulator.

PROPERTIES

- Good dilution capacity
- Good cleaning power
- Medium-slow evaporation rate
- Provides good adhesion without removing the underlying layer of the substrate

TECHNICAL DATA

CLASSIFICATION		
APPEARANCE	Liquid	
COLOUR	Clear Colourless	
COLOUR	Characteristics	
DENSITY	0.75 ± 0.03 g/ml	ISO 2811-1

APPLICATION PROCESS

Application

To adjust the application viscosity. Add to the varnish or paint in the proportion specified in the technical data sheet for the product in use. Stir the mixture by hand or using mechanical means (but slowly) until a completely homogeneous product is achieved. As a solvent for cleaning tools.

ADDITIONAL INFORMATION

Health and safety

For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject.

WASTE: HAZARDOUS. LER: 080111

Storage

The product will remain stable in its original, unopened packaging, at ambient temperatures not exceeding 30°C or falling below 5°C, for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed and undamaged packaging, and protected from frost and direct sunlight.

Tariff heading

TARIC code: 3814 00 90

Note

The data provided in this technical data sheet may be subject to change depending on possible variations in formulation and, in any case, represent indicative values which do not exempt the user from carrying out the necessary tests to ensure the product is suitable for a specific application.