



# Disolvente 376 para Esmalte Antioxidante

## SALES FORMAT

25L, 5L, 1L

### DESCRIPTION

A medium-fast drying solvent, specially formulated for TKROM Antioxidant Enamel. Suitable both for diluting the product and for cleaning brushes and tools.

### SCOPE OF APPLICATION

Specifically for the dilution of Antioxidant Enamel.

Tool cleaning.

Application viscosity regulator.

### PROPERTIES

- High dilution capacity
- High cleaning power
- Medium-fast drying speed
- Provides good adhesion without removing the underlying layer of the substrate

### TECHNICAL DATA

#### CLASSIFICATION

#### APPEARANCE

Liquid

#### COLOUR

Colourless transparent

#### COLOUR

Characteristics

#### DENSITY

0.86 ± 0.03 g/ml

ISO 2811-1

### APPLICATION PROCESS

#### Application

To adjust application viscosity. Add to the paint in the proportion indicated in the technical data sheet for the product in use. Stir the mixture manually or using mechanical means (but slowly) until a completely homogeneous product is achieved. As a solvent for cleaning tools.

### ADDITIONAL INFORMATION

#### Health and safety

For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject. WASTE: HAZARDOUS. LER: 080111

#### Storage

The product will remain stable in its original, unopened packaging at ambient temperatures not exceeding 30°C or falling below 5°C for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed and undamaged packaging, and protected from frost and direct sunlight.

#### Tariff heading

TARIC code: 3814 00 90

#### Note

The data provided in this technical data sheet may be subject to change depending on possible variations in formulation and, in any case, represent indicative values which do not exempt the user from carrying out the necessary tests to ensure the product is suitable for a specific application.