



DISOLVENTE 333 ANTISILICONAS

SALES FORMAT

1L

DESCRIPTION

Additive to prevent the formation of craters and surface defects in primers and enamels based on nitrocellulose, synthetics or polyurethanes. Add the anti-silicone additive to the diluent of the product in question and stir to ensure thorough mixing. Dosage: 2%–5%.

SCOPE OF APPLICATION

Specifically for paints with high surface tension

PROPERTIES

- High levelling power
- Formulated with a balanced blend of solvents and free from water and alcohols
- Medium-slow evaporation rate

TECHNICAL DATA

CLASSIFICATION

APPEARANCE	Liquid	
COLOUR	Clear Colourless	
COLOUR	Characteristics	
DENSITY	0.91 ± 0.02 g/ml	ISO 2811-1

APPLICATION PROCESS

Application

Add to the varnish or paint at a ratio of 2 to 5 per cent. Stir the mixture by hand or using mechanical means (but slowly) until a completely homogeneous product is achieved.

ADDITIONAL INFORMATION

Health and safety

For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject.

WASTE: HAZARDOUS. LER: 080111

Storage

The product will remain stable in its original, unopened containers at ambient temperatures not exceeding 30°C or falling below 5°C for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed and undamaged packaging, and protected from frost and direct sunlight.

Tariff heading

TARIC code: 3814 00 10

Note

The data provided in this technical data sheet may be subject to change depending on possible variations in formulation and, in any case, represent indicative values which do not exempt the user from carrying out the necessary tests to ensure the product is suitable for a specific application.