



DISOLVENTE 330 HIDROALCOHOLICO

SALES FORMAT

25L

DESCRIPTION

Special solvent for diluting hydroalcoholic wood tints.

Fully water-compatible.

SCOPE OF APPLICATION

Tool cleaning for products where this is recommended

PROPERTIES

- High cleaning power
- Average evaporation rate

TECHNICAL DATA

CLASSIFICATION

APPEARANCE

Liquid

COLOUR

Colourless Transparent

COLOUR

Features

DENSITY

0.84 ± 0.02 g/ml

ISO 2811-1

APPLICATION PROCESS

Application

To adjust the application viscosity. Add to the varnish or paint in the proportion specified in the technical data sheet for the product in use. Stir the mixture by hand or using mechanical means (but slowly) until a completely homogeneous product is achieved. As a solvent for cleaning tools.

ADDITIONAL INFORMATION

Health and safety

For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject.

WASTE: HAZARDOUS. LER: 080111

Storage

The product will remain stable in its original, unopened packaging, at ambient temperatures not exceeding 30°C or falling below 5°C, for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed and undamaged packaging, and protected from frost and direct sunlight.

Tariff heading

TARIC code: 3814 00 90

Note

The data provided in this technical data sheet may be subject to change depending on possible variations in formulation and, in any case, are indicative values only; they do not exempt the user from carrying out the necessary tests to ensure the product is suitable for a specific job.