



# DISOLVENTE LIMPIA UTILES

## SALES FORMAT

5L, 1L, 500ml

### DESCRIPTION

A solvent-based cleaner for tools, which allows brushes and rollers used to apply paints (oil-based or synthetic) to be cleaned by emulsifying with water, as well as removing grease, oil or dirt stains from all types of surfaces

### SCOPE OF APPLICATION

Suitable for cleaning tools and removing stains from all types of surfaces (aluminium, plastic, metals, etc.)

### PROPERTIES

- Water-dispersible
- Good cleaning power.
- Slow evaporation rate

### TECHNICAL DATA

#### CLASSIFICATION

APPEARANCE	Liquid	
COLOUR	Yellowish Transparent	
COLOUR	Features	
DENSITY	0.85 ± 0.02 g/ml	ISO 2811-1

### APPLICATION PROCESS

#### Application

Removing stains from metal surfaces: Apply the product undiluted. Removing stains from other types of surfaces: mix TKROM SOLVENT TOOL CLEANER with water (maximum ratio 1:1) and stir until a whitish emulsion forms. Tools and stains must still be damp, not dry, to facilitate cleaning. Cleaning stains (paint, grease or dirt) from metal surfaces: rub directly with a cloth soaked in TKROM TOOL CLEANING SOLVENT. Rinse with soapy water until the product has completely disappeared. Leave to dry. Cleaning stains (paint, grease or dirt) from other surfaces: apply the pre-emulsified product and rub the surface with a cloth. Rinse with water until the product has completely disappeared. Leave to dry. Cleaning tools (brushes and rollers): pour the appropriate amount of TKROM TOOL CLEANING SOLVENT into a container suitable for the size of the tool to be cleaned. Soak the tool by pressing it down until it is thoroughly saturated. Then add a little water and scrub the brush or roller in the resulting emulsion. Rinse thoroughly with plenty of water.

### ADDITIONAL INFORMATION

#### Health and safety

For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject.

WASTE: HAZARDOUS. LER: 080111

#### Storage

The product will remain stable in its original, unopened packaging at ambient temperatures not exceeding 30°C or falling below 5°C for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed and undamaged packaging, and protected from frost and direct sunlight.

#### Tariff heading

TARIC code: 3814 00 90

#### Note

The data provided in this technical data sheet may be subject to change depending on possible variations in formulation and, in any case, are indicative values only; they do not exempt the user from carrying out the necessary tests to ensure the product is suitable for a specific job.

