



# DISOLVENTE 360 ECOLOGICO MULTIUSOS

## SALES FORMAT

25L, 5L, 1L, 500ml

## DESCRIPTION

A solvent completely free from hydrocarbons, suitable for thinning all types of nitrocellulose, acrylic, epoxy, polyurethane, synthetic and oil-based products, etc. It possesses excellent solvent and degreasing power.

## SCOPE OF APPLICATION

Versatile for thinning a wide range of paints. For cleaning tools with products where recommended. A diluent for most synthetic industrial coatings. Adjusts application viscosity.

## PROPERTIES

- High dilution and cleaning power
- Provides good adhesion with a balanced evaporation rate
- Medium-slow evaporation rate

## TECHNICAL DATA

APPEARANCE	Liquid	
COLOUR	Colourless Transparent	
COLOUR	Features	
DENSITY	0.87 ± 0.03 g/ml	ISO 2811-1
REFRACTIVE INDEX	1,392-1,396	

## APPLICATION PROCESS

### Application

To adjust the application viscosity. Add to the varnish or paint in the proportion specified in the technical data sheet for the product being used. Stir the mixture by hand or using mechanical means (but slowly) until a completely homogeneous product is achieved. As a solvent for cleaning tools.

## ADDITIONAL INFORMATION

### Health and safety

For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject.

WASTE: HAZARDOUS. LER: 080111

### Storage

The product will remain stable in its original, unopened packaging at ambient temperatures not exceeding 30°C or falling below 5°C for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed and undamaged packaging, and protected from frost and direct sunlight.

### Tariff heading

TARIC code: 3814 00 90

### Note

The data provided in this technical data sheet may be subject to change depending on possible variations in formulation and, in any case, are indicative values only; they do not exempt the user from carrying out the necessary tests to ensure the product is suitable for a specific job.