



DISOLVENTE 310 POLIURETANO

SALES FORMAT

25L, 5L, 1L

DESCRIPTION

A blend of solvents formulated for the correct dilution and cleaning of polyurethane-based products, both aliphatic and aromatic. Particularly suitable for pigmented primers and topcoats, enabling the achievement of well-levelled surfaces free from orange peel.

SCOPE OF APPLICATION

Specifically for thinning 1- or 2-component polyurethane paints. For cleaning tools with products where recommended. Adjusts application viscosity.

PROPERTIES

- High dilution and cleaning power
- Slow evaporation rate
- Formulated with a balanced blend of solvents
- Facilitates levelling
- Does not interfere with the curing of the urethane

TECHNICAL DATA

CLASSIFICATION

APPEARANCE	Liquid	
COLOUR	Colourless Transparent	
COLOUR	Features	
DENSITY	0.90 ± 0.03 g/ml	ISO 2811-1
REFRACTIVE INDEX	1,400–1,402	

APPLICATION PROCESS

Application

As a viscosity regulator for application. Add to the varnish or paint in the proportion specified in the technical data sheet for the product in use, after curing. Stir the mixture by hand or using mechanical means (but slowly) until a completely homogeneous product is achieved. As a solvent for cleaning tools.

ADDITIONAL INFORMATION

Health and safety

For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject.

WASTE: HAZARDOUS. LER: 080111

Storage

The product will remain stable in its original, unopened packaging at ambient temperatures not exceeding 30°C or falling below 5°C for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed and undamaged packaging, and protected from frost and direct sunlight.

Tariff heading

TARIC code: 3814 00 10

Note

The data provided in this technical data sheet may be subject to change depending on possible variations in formulation and, in any case, are indicative values only; they do not exempt the user from carrying out the necessary tests to ensure the product is suitable for a specific job.

