



DISOLVENTE 345 SINTETICOS Y GRASOS

SALES FORMAT

25L, 5L, 1L, 500ml

DESCRIPTION

A blend of solvents specially formulated for use with all types of synthetic and oil-based enamels and paints, whether applied by brush, roller, spray gun or immersion.

SCOPE OF APPLICATION

Specifically for diluting synthetic and oil-based paints.

Tool cleaning for products where this is recommended.

Diluents for most synthetic industrial coatings.

Application viscosity regulator.

PROPERTIES

- High dilution and cleaning power
- Provides good adhesion without removing the underlying layer of the substrate
- Medium-fast evaporation rate

TECHNICAL DATA

APPEARANCE	Liquid	
COLOUR	Colourless Transparent	
COLOUR	Features	
DENSITY	0.85 ± 0.02 g/ml	ISO 2811-1
REFRACTIVE INDEX	1,474–1,476	

APPLICATION PROCESS

Application

To adjust the application viscosity. Add to the varnish or paint in the proportion specified in the technical data sheet for the product in use. Stir the mixture by hand or using mechanical means (but slowly) until a completely homogeneous product is achieved. As a solvent for cleaning tools.

ADDITIONAL INFORMATION

Health and safety

For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject.

WASTE: HAZARDOUS. LER: 080111

Storage

The product will remain stable in its original, unopened packaging, at ambient temperatures not exceeding 30°C nor falling below 5°C, for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed and undamaged packaging, and protected from frost and direct sunlight.

Tariff heading

TARIC code: 3814 00 90

Note

The data provided in this technical data sheet may be subject to change depending on possible variations in formulation and, in any case, represent indicative values which do not exempt the user from carrying out the necessary tests to ensure the product is suitable for a specific job.