



DISOLVENTE 331 TINTES NGR

SALES FORMAT

25L

DESCRIPTION

Fast-evaporating solvent, specifically designed for diluting non-aqueous wood tints.

SCOPE OF APPLICATION

Tool cleaning for products where this is recommended.

Diluent for non-aqueous wood tints.

PROPERTIES

- High cleaning power
- Rapid evaporation rate

TECHNICAL DATA

CLASSIFICATION

APPEARANCE	Liquid	
COLOUR	Colourless Transparent	
COLOUR	Features	
DENSITY	0.82 ± 0.02 g/ml	ISO 2811-1

APPLICATION PROCESS

Application

As a diluent for non-aqueous tints. As a solvent for cleaning tools.

ADDITIONAL INFORMATION

Health and safety

For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject.

WASTE: HAZARDOUS. LER: 080111

Storage

The product will remain stable in its original, unopened packaging at ambient temperatures not exceeding 30°C or falling below 5°C for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original packaging, which must be tightly sealed and undamaged, and protected from frost and direct sunlight.

Tariff heading

TARIC code: 3814 00 90

Note

The data provided in this technical data sheet may be subject to change depending on possible variations in formulation and, in any case, represent indicative values which do not exempt the user from carrying out the necessary tests to ensure the product is suitable for a specific job.