

# TKROM DISOLVENTE 376 ANTIOXIDANTE



## PRODUCT DESCRIPTION

Medium-fast evaporation thinner specifically formulated for the TKROM Rust-resistant Enamel (TDS-6401). Suitable for diluting the product and for cleaning brushes and tools.

## USES / SCOPE OF APPLICATION

- Specifically designed to dilute Rust-resistant Enamel TDS-6401.
- Tool Cleaning.
- Regulates application viscosity.

CONTAINER	SIZE
Metal	1 L

## CHARACTERISTICS / BENEFITS

- High dilution and cleaning power.
- Provides good anchoring without removing the underlying layer of the substrate.
- Medium-fast evaporation speed.

## PRODUCT PROPERTIES

APPEARANCE OF THE DRY FILM	VALUE	STANDARD	REPORT
APPEARANCE	Líquido		
COLOUR	Transparente Incoloro		
ODOUR	Característico		

PHYSICAL PROPERTIES	VALUE	STANDARD	REPORT
DENSITY	0,84 - 0,88 g/ml	UNE-EN ISO 2811-1	

## APPLICATION PROCESSES

PROCESS	INSTRUCTIONS
PRODUCT PREPARATION	
APPLICATION	<ul style="list-style-type: none"> <li>· As an adjuster for application viscosity.</li> <li>· Apply over the paint in the proportion indicated in the product's technical specifications.</li> <li>· Stir the mixture manually or mechanically (but slowly) until the product is completely homogenised.</li> <li>· As a solvent to clean tools.</li> </ul>
TOOL CLEANING	· (See application process)

## SAFETY

Users should refer to the labelling and the latest version of the product's Safety Data Sheet for any information regarding safety issues related to use, storage, transport and waste disposal. The Safety Data Sheet contains all of the physical, environmental and toxicological data on the product, and information on all other issues related to this topic.

SAFETY SHEET	LER CODE	WASTE TYPE
<a href="#">MSDS-6920</a>	08 01 11	HAZARDOUS

## STORAGE

When kept in its original unopened container at room temperatures below 30°C and above 5°C, the product will remain stable for 24 months from the date of manufacture.

It should be stored in a cool, dry place, in its original properly sealed and undamaged container, protected from frost and direct sunlight.

## TARIFF HEADING

TARIC code: 3814 00 90

**Note:** The data presented in this technical data sheet may be modified based on possible changes in formation. In any case, values are provided for information purposes only, and the suitability of the product for a certain job should always be tested.

tkrom<sup>®</sup>