

ACRYPLAS

FIXED TOTAL PRO

PRIMING



FORMAT: 15L / 4L

Water-based, acrylic-based wall fixative, suitable for consolidating all types of wall substrates or layers of old whitewashed paint, as well as for varnishing bricks, natural or artificial stone.

- Ö Interior and exterior
- Ö High holding power
- Ö Adhesion promoter
- Ö High adhesion
- Ö Absorption regulator
- Ö Good penetrating power
- Ö Good alkali resistance
- Ö Easy application
- Ö Breathable to water vapour

APPEARANCE/COLOUR	CLEAR	WHITE	
DENSITY	1,03± 0,05 Kg/L	1,64± 0,05 Kg/L	ISO 2811-1
PH	7-8		
THEORETICAL PERFORMANCE	14-18 m ² /L	12-14 m ² /L	ISO 23811
VISCOSITY	2± 5 Pa-s (20rpm, R6)	23± 3 Pa-s (20rpm, R6)	ASTM D 2196- ASTM D 2196-10
SOLIDS IN VOLUME	25± 2	68± 2	ISO 23811
MAX. CONTENT COV PERMITTED/PRODUCT	30 g/l / <1 g/l	30 g/l / <30 g/l	2004/42/IIA

TOUCH-DRYING	15-30 MIN
REPOINTING	4-6 HOURS
TARIC CODE	3209 10 00
SAFETY DATA SHEET	MSDS - 0722
TYPE OF WASTE	NON DANGEROUS

1) Ensure that the substrate is compact and firm. **2)** Stir until the product is well homogenised. **3)** Respect the drying times between coats. **4)** Clean the tools with water immediately after use. **5)** It is not recommended to wash the walls until 24 days after application.

SYSTEM	PRODUCT	PERFORMANCE	DILUTION	LAYERS
PRIMING	FIXATIVE TOTAL PRO TRANSPARENT	14-18 m ² /l	1:3 WATER	1
PRIMING	FIXATIVE TOTAL PRO WHITE	12-14 m ² /l	5:1 WATER	1 o 2

The data indicated in this technical data sheet may be modified according to possible variations in formulation and, in any case, express indicative values which do not exempt from carrying out the appropriate tests on the suitability of the product for a specific job.

