

ACRYPLAS ELASTIC WATERPROOFING PROFESSIONAL COATING

FORMAT: 15L / 4L

An asphalt-free waterproof coating, which dries to provide a continuous, thick film coating that prevents any water seepage onto the surfaces it protects.

- ✓ High flexibility
- ✓ Tensile strength
- ✓ Alkalinity resistance
- ✓ High adhesion
- ✓ Suitable for horizontal and vertical surfaces



FINISH	MATE	UNE-EN 13300
COLOUR	WHITE / RED	
DENSITY	1,35± 0,05 Kg/L	ISO 2811-1
PH	8,5 - 9,2	
THEORETICAL PERFORMANCE	1.5-2.5 m²/L (200 microns dry)	ISO 23811
BERGER WHITENESS (WHITE)	106± 2	UNE 48073
VISCOSITY	40± 5 Pa-s (20rpm, R6)	ASTM D 2196-10
SOLIDS IN VOLUME	41± 2	ISO 23811
MAX. CONTENT COV PERMITTED/PRODUCT	140 g/l / <5 g/l	2004/42/IIA

TOUCH-DRYING	4 - 8 HOURS
REPOINTING	24 HOURS
TOTAL DRYING	10 - 15 DAYS
TARIC CODE	3209 10 00
SAFETY DATA SHEET	MSDS - 0206
TYPE OF WASTE	NON DANGEROUS

1) Ensure that the substrate is compact and firm. **2)** Stir until the product is well homogenised. **3)** Respect the drying times between coats. **4)** Clean the tools with water immediately after use. **5)** It is not recommended to wash the walls until 24 days after application.

SYSTEM	PRODUCT	PERFORMANCE	DILUTION	LAYERS
FINISH	ACRYPLAS WATERPROOFING ELASTIC	1.5-2.5 m²/l	0 % WATER	2

The data indicated in this technical data sheet may be modified according to possible variations in formulation and, in any case, express indicative values which do not exempt from carrying out the appropriate tests on the suitability of the product for a specific job.

tkrom.com



by
tkrom
pinturas